

Avro "WOLFPACK" Rivet Hammer

The Avro "WOLFPACK" series of riveting hammers feature a revolutionary piston design that delivers far more power and assists in absorbing vibration, allowing the operator to choose a smaller and lighter tool for the same application.

The "ERGONOMIC" housing is designed for maximum operator comfort and the "ERGO GRIP" which acts as a thermal protector and helps isolate vibration, are both standards in these tools. A spool valve system delivers slow, heavy blows necessary to drive rivets. An extremely sensitive teasing throttle permits precise control.



WP700 Shown

MODEL	CAPACITY Alu/Steel	BLOWS/Minute	BORE & STROKE in mm	LENGTH in mm	WEIGHT lb kg
WP500 RIVET HAMMER 5X .498 SHANK DIAMETER					
10055	1/4" / 3/16" (6.4mm 4.8mm)	1800	3/4" x 2-11/16" 19.1 x 68.3	8-5/16" 227	4-3/4 2.2
WP700 RIVET HAMMER 7X .498 SHANK DIAMETER					
10075	3/8" / 5/16" (9.5mm 7.9mm)	900	3/4" x 5-13/16" 19.1 x 147.6	11-15/16" 303	6 2.7
WP900 RIVET HAMMER 9X .498 SHANK DIAMETER					
10095	5/16" / 1/4" (7.9mm 6.4mm)	1150	3/4" x 3-7/8" 19.1 x 98.4	9-15/16" 252	5-1/8" 2.3

Standard Equipment: Beehive retainer #A92012

General: Air Inlet 1/4" NPT Standard
1/4" BSP (Europe) ADD-E to part number; eg: 10055E

Use 5/16" (8mm) I.D Hose
All tools rated at 90 psi (620 KPA) air pressure.

Safety Precaution: Read and follow all safety operating instructions.

WARNING: Excessive or improper use may result in carpal tunnel syndrome ("White Finger") disease.

Face and eye protection must be worn while operating power tools, per ANSI B186.1



4175 boul. Poirier
Montréal, Québec, Canada
H4R 2G9

T: 514.336.9444 | 1 866 874.9444

F: 514.336.0277 | 1 888 336.6055

www.avrotools.com

info@avrotools.com