

Standard and Vibration Reduced Riveting Hammers



Air inlet thread: 1/4" NPT/BSP

PIC REF	MODEL	PART NUMBER	AIRFRAME REF	BLOW PER MINUTE	BORE AND STROKE		ENERGY PER BLOW		CHISEL SHANK OPENING	CAPACITY COLD RIVETS		WEIGHT		HOSE INT. Ø	
					mm	J	ft.lb	Dural		Steel	kg	lb	mm	in.	
RIVETING HAMMERS (PISTOL GRIP) - STANDARD															
A	CP4444-RURAB	T022961	2X	2580	12.7 x 50.8mm 1/2" x 2"	4.0	2.9	TYPE 1 0.401"	3.2mm 1/8"	2.4mm 3/32"	1.0	2.2	10	3/8	
A	CP4444-RUSAB	T022962	3X	2160	12.7 x 76.2mm 1/2" x 3"	6.1	4.5	TYPE 1 0.401"	4.8mm 3/16"	4.0mm 5/32"	1.1	2.3	10	3/8	
A	CP4444-RUTAB	T022963	4X	1740	12.7 x 101.6mm 1/2" x 4"	8.1	6.0	TYPE 1 0.401"	6.4mm 1/4"	4.8mm 3/16"	1.3	2.7	10	3/8	
B	CP4447-RUSAB	T022965	5XB	1560	19.1 x 68.3mm 3/4" x 2 11/16"	12.3	9.1	TYPE D 0.498"	6.4mm 1/4"	4.8mm 3/16"	2.2	4.7	10	3/8	
B	CP4447-RUTAB	T022912	9XB	1140	19.1 x 98.4mm 3/4" x 3 7/8"	17.8	13.1	TYPE D 0.498"	7.9mm 5/16"	6.4mm 1/4"	2.3	5.1	10	3/8	
B	CP4447-RUVAB	T022964	7XB	900	19.1 x 147.6mm 3/4" x 5 13/16"	26.6	19.6	TYPE D 0.498"	9.5mm 3/8"	7.9mm 5/16"	2.7	9.0	10	3/8	
RIVETING HAMMERS (PISTOL GRIP) - VIBRATION REDUCED															
C	CP4450-2	T025189	2X	2580	12.7 x 50.8mm 1/2" x 2"	4.0	2.9	TYPE 1 0.401"	3.2mm 1/8"	2.4mm 3/32"	1.2	2.7	10	3/8	
C	CP4450-3	T025190	3X	2160	12.7 x 76.2mm 1/2" x 3"	6.1	4.5	TYPE 1 0.401"	4.8mm 3/16"	4.0mm 5/32"	1.3	2.8	10	3/8	
C	CP4450-4	T025191	4X	1740	12.7 x 101.6mm 1/2" x 4"	8.1	6.0	TYPE 1 0.401"	6.4mm 1/4"	4.8mm 3/16"	1.5	3.2	10	3/8	
D	CP4475-3	T025241	5XB	2000	19.1 x 76.2mm 3/4" x 3"	13.7	10.1	TYPE D 0.498"	6.4mm 1/4"	4.8mm 3/16"	1.8	3.9	10	3/8	
D	CP4475-4	T025242	9XB	1700	19.1 x 101.6mm 3/4" x 4"	18.3	13.5	TYPE D 0.498"	7.9mm 5/16"	6.4mm 1/4"	2.4	5.3	10	3/8	
D	CP4475-6	T025243	7XB	1250	19.1 x 152.4mm 3/4" x 6"	27.5	20.3	TYPE D 0.498"	9.5mm 3/8"	7.9mm 5/16"	2.8	6.2	10	3/8	
RIVETING HAMMERS (IN-LINE) - VIBRATION REDUCED															
E	CP4450-S-2	205 146 712 4	2X	2580	12.7 x 50.8mm 1/2" x 2"	4.0	2.9	TYPE 1 0.401"	3.2mm 1/8"	2.4mm 3/32"	1.25	2.8	10	3/8	
E	CP4450-S-3	205 146 713 4	3X	2160	12.7 x 76.2mm 1/2" x 3"	6.1	4.5	TYPE 1 0.401"	4.8mm 3/16"	4.0mm 5/32"	1.35	3.0	10	3/8	
E	CP4450-S-4	205 146 714 4	4X	1740	12.7 x 101.6mm 1/2" x 4"	8.1	6.0	TYPE 1 0.401"	6.4mm 1/4"	4.8mm 3/16"	1.45	3.2	10	3/8	