

CWR WRENCHES

CWR 'CLICK' WRENCH SERIES

- Wide range from 2 Nm up to 300 Nm.
- Very small sizes ideal for tightening in limited space.
- Repeatability of $\pm 4\%$.
- Easy and safe adjusting and handling.
- Standard drive (9x12 or 14x18) for a wide range of suitable end fittings.



CWR-20

MICROSWITCH ADAPTOR

- Upgrades CWR wrenches into signal transmitting devices.
- Easy support of control functionalities as batch counting and line control.



CWR-200

Model	Torque range		Length mm	Weight		Ø mm	Drive	Ordering No.
	Nm	ft lb		kg	lb			
CWR models								
CWR-20	3-20	2.2-14.8	129	0.248	0.547	21	9x12	8439 0041 00
CWR-25	2-25	1.5-18.4	174	0.288	0.635	21	9x12	8439 0041 01
CWR-50	5-50	3.7-37	236	0.466	1.027	21	9x12	8439 0041 02
CWR-85	15-85	11-62.7	305	0.576	1.270	21	9x12	8439 0041 03
CWR-120	50-120	37-88.5	349	0.666	1.468	24	9x12	8439 0041 04
CWR-200	50-200	37-148	419	0.916	2.019	30x26	14x18	8439 0041 05
CWR-300	60-300	44.2-221	685	1.366	3.012	32x28	14x18	8439 0041 06
Microswitch adaptor								
Microswitch adaptor kit for BWR-240 D								4027 5009 93
Microswitch adaptor kit for BWR-440 D								4027 5009 94
Microswitch	–	–	60	0.111	0.245	42	M18x1.5	4027 5015 90
Helix cable	–	–	2-6	0.341	0.752	–	–	8439 0030 00
Hook spanner			42					4027 5015 89



Microswitch adaptor



CWR with Microswitch adaptor