

ETD AND QMC

Model	Torque range soft joint		Speed	Length	Overall width	Weight		Bit drive	Ordering No.
	cNm	in lb				kg	lb		
Hand-held current controlled, without push-to-start									
ETD M 08 ABL V2	2-8	0.18-0.7	1350	185	29	0.30	0.66	HM 4 mm	8432 0815 18
ETD M 20 ABL V2	5-20	0.44-1.77	900	185	29	0.30	0.66	HM 4 mm	8432 0815 21
ETD M 27 ABL V2	7.5-27	0.66-2.4	900	185	29	0.30	0.66	HM 4 mm	8432 0815 27
Hand-held current controlled, push-start configurable									
ETD M 50 ABL V2	15-50	1.33-4.4	1000	238	36	0.61	1.37	HM 4 mm	8432 0815 50
ETD M 80 ABL V2	20-80	1.77-7.1	1100	238	36	0.61	1.37	HM 4 mm	8432 0815 80
ETD M 120 ABL V2	30-120	2.7-10.6	900	240	43	0.65	1.43	1/4" Hex	8432 0815 82
ETD M 200 ABL V2	50-200	4.42-17.7	700	240	43	0.65	1.43	1/4" Hex	8432 0815 84
ETD M 250 ABL V2	75-250	6.64-22.13	700	240	43	0.65	1.43	1/4" Hex	8432 0815 86
NOTE: Ordering number for screwdriver only. Tool cable, controller and PSU need to be ordered separately.									
Fixtured current controlled									
QMC21-05-HM4 *a	1.2-5	0.11-0.44	2000	123	57	0.2	0.44	HM 4mm	8432 0844 05
QMC21-10-HM4	3-10	0.27-0.89	2000	178	57	0.3	0.66	HM 4mm	8432 0844 10
QMC21-25-HM4	5.5-25	0.49-2.2	1000	178	57	0.3	0.65	HM 4mm	8432 0844 25
QMC41-50-HM4	12.5-50	1.1-4.4	2000	200	66	0.6	1.32	HM 4mm	8432 0844 52
QMC41-100-HM4	25-100	2.2-8.9	2000	200	66	0.6	1.32	HM 4mm	8432 0844 53
QMC41-50-I06	12.5-50	1.1-4.4	2000	205	66	0.61	1.36	1/4" Hex	8432 0844 61
QMC41-100-I06	25-100	2.2-8.9	2000	205	66	0.61	1.36	1/4" Hex	8432 0844 62
QMC41-150-I06	37.5-150	3.3-13.3	1000	213	66	0.625	1.38	1/4" Hex	8432 0844 63
QMC41-250-I06	62.5-250	5.5-22.1	750	224	66	0.650	1.43	1/4" Hex	8432 0844 64
*a Only compatible with MTF6000.									
NOTE: Ordering number for screwdriver only. Tool cable, controller and PSU need to be ordered separately.									
Soft-stop reporting models									
ETD MT 21-25-HM4	5-25	0.44-2.21	1000	226	32	0.35	0.77	HM 4 mm	8432 0845 25
ETD MT 41-50-HM4	10-50	0.9-4.4	2000	248	34	0.60	1.32	HM 4 mm	8432 0845 50
ETD MT 41-100-HM4	20-100	1.8-8.9	2000	248	34	0.60	1.32	HM 4 mm	8432 0845 60
ETD MT 41-50-I06	10-50	0.9-4.4	2000	254	34	0.65	1.43	1/4" Hex	8432 0845 51
ETD MT 41-100-I06	20-100	1.8-8.9	2000	254	34	0.65	1.43	1/4" Hex	8432 0845 61
ETD MT 41-150-I06	30-150	2.7-13.3	1000	254	34	0.65	1.43	1/4" Hex	8432 0845 70
ETD MT 41-250-I06	50-250	4.4-22.1	750	254	34	0.65	1.43	1/4" Hex	8432 0845 80