

TENSOR SRB31 AND TBP

SRB31

The SRB reports wirelessly to the Power Focus 6000 system and takes full advantage of Virtual Stations, able to perform low reaction strategies as TurboTight and Tensor Pulse, and traditional strategies as the two steps.

- Operator feedback and battery status via LED indicator.
- A buffer battery makes battery swaps trouble free.
- Integrated indicator on the battery shows battery and health status.
- Dual antenna.
- Rapid Backup Unit (RBU) functionality.



Model	Square drive In	Torque range Nm	ft lb	Battery	Speed r/min	Weight kg	Weight incl battery kg	Length mm	CS distance mm	Ordering No.
Transducerized Tensor SRB										
ETP SRB31-20-10	3/8	5-20	3.7-14.7	18/36 V	1500	1.15	1.65	212	211	8433 3270 30
ETP SRB31-20-I06	3/8	5-20	3.7-14.7	18/36 V	1500	1.15	1.65	212	211	8433 3270 31
ETP SRB31-25-10	3/8	6-25	4.4-18.4	18/36 V	1500	1.15	1.65	223	211	8433 3260 30
ETP SRB31-25-I06	3/8	6-25	4.4-18.4	18/36 V	1500	1.15	1.65	223	211	8433 3260 31