



Model	Max free speed r/min	Max output kW	Max wheel dia mm	Spindle thread	Spindle length mm	Weight kg	Height over spindle mm	Air consumption at max output l/s	Air consumption at free speed l/s	Rec hose size mm	Air inlet thread BSP in	Air inlet thread NPT	Ordering No.
GTG25-F120-13	12000	2.5	125	-	-	2.1	61	34	9	16	3/8	-	8423 2525 01
GTG25-F085-18	8500	2.5	180	-	-	2.2	61	34	9	16	3/8	-	8423 2525 02
GTG25-F120-527	12000	2.5	125	5/8"-11 UNC	23.4	2.2	84	34	9	16	-	3/8	8423 2525 06
GTG25-F085-727	8500	2.5	180	-	-	2.4	84	34	9	16	-	3/8	8423 2525 07
GTG25 F120-M14	12000	2.5	125	M14	20	2.1	80	34	9	16	3/8	-	8423 2525 10
GTG25 F085-M14	8500	2.5	180	M14	20	2.2	80	34	9	16	3/8	-	8423 2525 11
GTG25 F085-13	8500	2.5	125	-	-	2.2	61	34	9	16	3/8	-	8423 2525 15

North American Model

Accessories

	8423 2525 01	8423 2525 02	8427 2525 06	8428 2525 07	8430 2525 10	8431 2525 11	8423 2525 15	Ordering No.
Included								
Allen key for flange nut	✓	✓	-	-	-	-	✓	4080 0048 00
Allen key for support handle	✓	✓	✓	✓	-	-	✓	0902 0113 00
Flange washer (for grinding applications)	✓	✓	-	-	-	-	✓	4175 0777 90
Flange washer (for cutting-off applications)	✓	✓	-	-	-	-	✓	4175 0777 92
Face spanner (30 x Ø5.5 mm)	-	-	✓	✓	-	-	-	4080 0201 00
Face spanner	-	-	-	-	✓	✓	-	4080 0862 00
Locking kit (imperial)	-	-	✓	✓	-	-	-	4170 1188 91
Locking kit (metric)	-	-	-	-	✓	✓	-	4170 1188 90
Adapter (Ø42mm)	-	-	-	✓	-	-	-	4175 0643 02
Adapter (Ø84mm, 5/8" - type 27 and 42 wheels)	-	-	-	✓	-	-	-	4175 0646 00