



| Model          | Max<br>free<br>speed | Max<br>pad<br>dia | Spindle<br>thread | Spindle<br>length | Height<br>over<br>spindle | Max<br>output | Weight | Air con-<br>sumption<br>at<br>max<br>output | Air con-<br>sumption<br>at<br>free<br>speed | Rec<br>hose<br>size | Air inlet<br>thread<br>BSP | Air inlet<br>thread<br>NPT | Ordering No. |
|----------------|----------------------|-------------------|-------------------|-------------------|---------------------------|---------------|--------|---------------------------------------------|---------------------------------------------|---------------------|----------------------------|----------------------------|--------------|
|                | r/min                | mm                |                   | mm                | mm                        | kW            | kg     | l/s                                         | l/s                                         | mm                  | in                         | in                         |              |
| GTG25-S085     | 8500                 | 180               | 5/8"-11 UNC       | 23.4              | 84                        | 2.5           | 2.0    | 34                                          | 9                                           | 16                  | 3/8                        | -                          | 8423 2525 03 |
| GTG25-S085-M14 | 8500                 | 180               | M14               | 23.4              | 84                        | 2.5           | 2.0    | 34                                          | 9                                           | 16                  | 3/8                        | -                          | 8423 2525 04 |
| GTG25-S085-700 | 8500                 | 180               | 5/8"-11 UNC       | 23.4              | 84                        | 2.5           | 1.9    | 34                                          | 9                                           | 16                  | -                          | 3/8                        | 8423 2525 08 |

North American Model

## Accessories

|                                              | 8425 2525 03 | 8426 2525 04 | 8429 2525 08 | Ordering No. |
|----------------------------------------------|--------------|--------------|--------------|--------------|
| <b>Included</b>                              |              |              |              |              |
| Allen key for flange nut                     | ✓            | -            | -            | 4080 0048 00 |
| Allen key for support handle                 | ✓            | ✓            | ✓            | 0902 0113 00 |
| Face spanner (30 x Ø5.5 mm)                  | ✓            | ✓            | ✓            | 4080 0201 00 |
| Locking kit (imperial)                       | ✓            | -            | ✓            | 4170 1188 91 |
| Locking kit (metric)                         | -            | ✓            | -            | 4170 1188 90 |
| <b>Optional</b>                              |              |              |              |              |
| Whip hose kit (3/8" + RUBAIR16)              | ✓            | ✓            | ✓            | 4175 0738 90 |
| Productivity kit (MIDI-FRL-1/2-BSP EQ10-T13) | ✓            | ✓            | ✓            | 8202 0850 17 |
| MULTIFLEX-3/8 cover                          | ✓            | ✓            | ✓            | 8202 1350 42 |
| MULTIFLEX-3/8                                | ✓            | ✓            | ✓            | 8202 1350 22 |
| Dust extraction kit                          | ✓            | ✓            | ✓            | 3780 4090 27 |
| Lever, compl.                                | ✓            | ✓            | -            | 4150 1594 98 |
| Pad (backing pad, UNC 5/8" thread)           | ✓            | -            | ✓            | 4170 1192 90 |
| Pad (Spiralcool backing pad, M14 thread)     | -            | ✓            | -            | 4170 1192 91 |