

IXB – BATTERY TOOLS WITH INTEGRATED CONTROLLER

The first transducerized battery tools without the need of an external controller in Atlas Copco portfolio with a full scope of PF6-like features and benefits.

Consisting of two most advanced transducerized battery tools that bring countless number of possibilities for modern production built on Industry 4.0 principles.

Available in five variants:

- ITB-A - angle models
- ITB-P - pistol models
- ITB-S - straight models
- ICB-A - compact angel models
- ICB-Q - quick change angle gear compact models



MAIN TECHNICAL PARAMETERS

Accuracy:	2 types of a transducer: ± 3,5 % according to ISO 5393; ± 5 % according to ISO 5393
Torque Range:	ITB – Integrated controller Transducerized Battery tool: 1 – 200 Nm ICB – Integrated controller Compact transducer Battery tool: 1,5 – 20 Nm
Speed:	ITB: up to 2972 RPM; ICB: up to 1200 RPM; possible change during operation
Connectivity	USB, Wi-Fi, Open Protocol, Digi I/O (by using I/O hub)
Virtual Station types	Station Control, Critical Control, Process Control
Tightening programs	Up to 1000 Psets; Up to 250 Batch sequences; Multistep
Target parameters	Torque, angle, based on actual joint characteristics – seating strategy, yield strategies
Control parameters	Torque, angle (rotation), speed, seating point, yield point
Results memory	10 000 results 10 000 graphs

FEATURES

- Controller integrated in a tool
- Virtual stations concept
- Features Management concept (scaling functionality)
- Advanced tightening strategies
- Snag gradient – seating strategy
- Multistep strategy
- Full traceability
- Industry 4.0 ready
- Wireless connectivity (Wi-Fi and Bluetooth)
- Improved tool speed
- Wide range of a tool / station accessories
- Can be connected to Power Focus 6000 and Power Focus 8

BENEFITS

- Fast, stable and reliable communication / data collection (improved wireless performance)
- Space savings (no HW controller needed)
- Lower installation costs (easier installation processes)
- Smart flexibility (while building a production line / rebalancing)
- Easier joint accessibility (adjustable tool head)
- Comfortable ergonomics (adjustable tool trigger, reduced tool weight and size)
- Improved productivity (tool speed)
- Fast and easy tool management (modern & user-friendly SW)
- Reduction of defects and repairs (advanced tightening strategies, error-proofing)

Model	Battery V	Torque range Nm	Max speed rpm	Output shaft type In	Weight incl battery kg	Length mm	Width mm	Angle head	Ordering No.
ITB-P31-06-I06	14 V & 18 V	1.2 -6	1990	1/4 in	1.5 kg	209.4	74.5	Pistol	8436 0130 08
ITB-P31-06-10	14 V & 18 V	1.2 -6	1990	sq. 3/8 in	1.5 kg	209.4	74.5	Pistol	8436 0130 07
ITB-P31-12-I06	14 V & 18 V	2.4 - 12	1480	1/4 in	1.5 kg	209.4	74.5	Pistol	8436 0130 14
ITB-P31-12-10	14 V & 18 V	2.4 - 12	1480	sq. 3/8 in	1.5 kg	209.4	74.5	Pistol	8436 0130 13