



Model	Max free speed r/min	Max bev- el width mm	Max radius mm	Max output kW	Weight kg	Max height over guide plate mm	Air consumption at max output l/s	Air consumption at free speed l/s	Rec hose size mm	Air inlet thread BSP in	Ordering No.
LSB39 S085	8500	8	4	1.8	2.6	111	29.5	16.3	13	3/8	8423 0133 10

Accessories

	Ordering No.
Included	
Milling head (Chamfer 45°)	4150 2240 90
Guide bearing (Chamfer 45°)	4150 2240 93
Insert (Chamfer 45°)	4150 2241 92
Optional	
Hose kit (Turbo 13; 13 mm (1/2"), L = 0.9m (L = 3 ft))	4150 1618 81
Hose (Soft type, Ø 38mm, L = 1 m)	4150 1314 02
Hose (HD type, Ø 42mm, L = 1 m)	4150 1532 01
Milling head (Radius 2mm, 3mm, 4mm)	4150 2240 90
Milling head (Chamfer 30°)	4150 2240 94
Milling head (Chamfer 35°)	4150 2240 98
Milling head (Chamfer 55°)	4150 2240 96
Milling head (Chamfer 60°)	4150 2241 04
Guide bearing (Radius 2mm)	4150 2240 80
Guide bearing (Radius 3mm)	4150 2240 91
Guide bearing (Radius 4mm)	4150 2240 92
Guide bearing (Chamfer 30°)	4150 2240 95