



Model	Max free speed r/min	Max output kW	Collet size mm	Length mm	Weight kg	Air consumption at max output l/s	Air consumption at free speed l/s	Rec hose size mm	Air inlet thread BSP	Scatter damped	Ordering No.
LSF12 S200-1	20000	0.24	6	170	0.36	8.1	2.6	8	1/4	No	8423 1124 01
LSF12 S250-1	25000	0.292	6	170	0.36	8.5	3.4	8	1/4	No	8423 1124 02
LSF12 S310-1	31000	0.323	6	170	0.36	9.2	4.2	8	1/4	No	8423 1124 03
LSF12 S400-1	40000	0.358	6	170	0.36	9.8	7.0	8	1/4	No	8423 1124 04

Accessories

	8423 1124 01	8423 1124 02	8423 1124 03	8423 1124 04	Ordering No.
Included					
Open-end spanner (A/F 11mm)	✓	✓	✓	✓	4150 2226 14
Open-end spanner (17mm)	✓	✓	✓	✓	4150 2226 13
Collet (Ø5.55 to 6.35 mm - Ø1/4")	✓	✓	✓	✓	4150 2226 03
Optional					
Hose kit (Cablaire 08; 8 mm (5/16"), L = 0.9 m (L = 3 ft))	✓	✓	✓	✓	4150 1689 80
Collet (Ø7/32")	✓	✓	✓	✓	4150 2226 49
Collet (Ø3mm - Ø1/8")	✓	✓	✓	✓	4150 2226 46
Collar	✓	✓	✓	✓	4150 2226 02
Collet holder	✓	✓	✓	✓	4150 2226 21
Collet nut	✓	✓	✓	✓	4150 2226 04
Productivity kit (MIDI-FRL-1/2-BSP EQ08-C10)	✓	✓	✓	✓	8202 0850 03
MULTIFLEX-1/4 cover	✓	✓	✓	✓	8202 1350 41
MULTIFLEX-1/4-NPT (For North America)	✓	✓	✓	✓	8202 1350 26
MULTIFLEX-1/4	✓	✓	✓	✓	8202 1350 20