

LSR64

Rough Grinding and Cutting

Straight Grinders



Model	Max free speed r/min	Max output kW	Length mm	Weight kg	Air consumption at max output l/s	Air consumption at free speed l/s	Rec hose size mm	Air inlet thread BSP	Wheel Diameter (DxTxH) ^a mm	Ordering No.
LSR64 S041	4100	1.6	535	5.4	29	7	16	1/2	-	8423 1640 14 (for wire brushes)
LSR64 S060-15	6000	2.3	535	5.4	41	11	16	1/2	150x25x16	8423 1640 22
LSR64 S072-13	7200	2.5	535	5.4	45	14	16	1/2	125x25x16	8423 1640 30
LSR64 S100-15	10000	2.9	535	5.8	53	26	16	1/2	150x25x25	8423 1640 55

^aDxTxH = Diameter x Thickness x Hole

Accessories

	8423 1640 14	8423 1640 22	8423 1640 30	8423 1640 55	Ordering No.
Included					
Face spanner (A/F 27mm - 1 1/16" Type B)	✓	-	-	-	0902 0427 00
Face spanner (30mm)	-	✓	✓	✓	4080 0201 00
Rear flange (wheel inner Ø16mm)	✓	✓	✓	-	4150 0619 00
Rear flange (wheel inner Ø25mm)	-	-	-	✓	4150 0713 00
Flange nut	✓	✓	✓	✓	4150 0670 00
Front washer	✓	✓	✓	✓	4150 0671 00
Optional					
Steel wire brush Ø115mm	✓	-	-	-	4170 0491 00
Rear flange (wheel inner Ø16mm)	-	-	-	✓	4150 0619 00
Rear flange (wheel inner Ø20mm)	✓	✓	✓	✓	4150 1650 00
Rear flange (wheel inner Ø25mm)	✓	✓	✓	-	4150 0713 00
Productivity kit (MIDI-FRL-1/2-BSP EQ10-T16)	✓	✓	-	-	8202 0850 12
Productivity kit (MAXI-F/R-1-BSP T 1/2" BSP)	-	-	✓	✓	8202 0850 05
MULTIFLEX-1/2-HF	✓	✓	✓	✓	8202 1350 60