



Model	Max free speed	Max pad size	Orbit dia	Height over spindle	Air inlet thread BSP	Max output	Weight	Air consumption at free speed	Rec hose size	Handle		Ordering No.
	r/min	mm	mm	mm	in	W	kg	l/s	mm	With	Without	
LST20 R350 (standard model)	12000	90	5	93	1/4	200	0.85	8	8	-	•	8423 0361 65
LST20 R550 (standard model)	12000	125	5	83	1/4	200	0.85	8	8	-	•	8423 0361 69
LST20 R650 (standard model)	12000	150	5	83	1/4	200	0.85	8	8	-	•	8423 0361 73
LST20 R525 (standard model)	12000	125	2.4	83	1/4	200	0.85	8	8	-	•	8423 0361 81
LST20 R625 (standard model)	12000	150	2.4	83	1/4	200	0.85	8	8	-	•	8423 0361 84

Accessories

	8423 0361 65	8423 0361 69	8423 0361 73	8423 0361 81	8423 0361 84	Ordering No.
Included						
Pad velcro - Ø150mm (6")	-	✓	-	✓	-	4112 0795 02
Pad velcro - Ø150mm (6")	-	-	✓	-	✓	4112 1214 00
Pad velcro - Ø89mm (3 1/2")	✓	-	-	-	-	4112 1218 00
Hose nipple for 6.3mm (1/4") hose	✓	✓	✓	✓	✓	9000 0241 00
Wrench (26mm)	✓	✓	✓	✓	✓	4112 1241 00
Optional						
Pad self stick paper - Ø150mm (6")	-	-	✓	-	✓	4112 1235 00
Pad self stick paper - Ø125mm (5")		✓	-	✓	-	4112 1233 00
Adapter - Ø1" / 1 1/4"	✓	✓	✓	✓	✓	4112 1220 00
Maintenance tool, compl.	✓	✓	✓	✓	✓	4080 1156 90
Dust extraction hose - L=1.5m (60")	✓	✓	✓	✓	✓	4112 1227 00
Dust Extraction Hose, 1.8 m - Ø25 mm for 125 m3/h suction requirement	✓	✓	✓	✓	✓	3780 2724 20
Dust Extraction Hose, 1.8 m - Ø32 mm for 200 m3/h suction requirement	✓	✓	✓	✓	✓	3780 2724 31
Dust Extraction Hose, 1.8 m - Ø38 mm for 250 m3/h suction requirement	✓	✓	✓	✓	✓	3780 2724 40
MULTIFLEX-1/4-NPT (For North America)	✓	✓	✓	✓	✓	8202 1350 26
MULTIFLEX-1/4 cover	✓	✓	✓	✓	✓	8202 1350 41
MULTIFLEX-1/4	✓	✓	✓	✓	✓	8202 1350 20
Productivity kit (MIDI-FRL-1/2-BSP EQ08-C10)	✓	✓	✓	✓	✓	8202 0850 03