



Model	Max free speed	Max pad size	Orbit dia	Height over spindle	Air inlet thread BSP	Max output	Weight	Air consumption at free speed	Rec hose size	Handle		Ordering No.
	r/min	mm	mm	mm	in	W	kg	l/s	mm	With	Without	
LST32 H090-15 (central suction - Required air flow 150 m3/h or 88 cfm)	9000	150	8	121	1/4	300	1.4	7.5	8	•	-	8423 0362 55
LST32 S090-15 (central suction - Required air flow 150 m3/h or 88 cfm)	9000	150	8	118	1/4	300	1.3	7.5	8	-	•	8423 0362 71

Accessories

	8423 0362 55	8423 0362 71	Ordering No.
Included			
Pad velcro - Ø150mm (6") with 6 holes	✓	✓	4112 1215 00
Lever for changing pad	✓	✓	4112 0779 00
Hose nipple for 8mm (5/16") hose	✓	✓	9090 1715 00
Optional			
Dust Extraction Hose, 1.8 m - Ø25 mm for 125 m3/h suction requirement	✓	✓	3780 2724 20
Dust Extraction Hose, 1.8 m - Ø32 mm for 200 m3/h suction requirement	✓	✓	3780 2724 31
Dust Extraction Hose, 1.8 m - Ø38 mm for 250 m3/h suction requirement	✓	✓	3780 2724 40
MULTIFLEX-1/4-NPT (For North America)	✓	✓	8202 1350 26
MULTIFLEX-1/4 cover	✓	✓	8202 1350 41
MULTIFLEX-1/4	✓	✓	8202 1350 20
Productivity kit (MIDI-FRL-1/2-BSP EQ08-C10)	✓	✓	8202 0850 03