



Model	Max free speed r/min	Max pad dia mm	Spindle thread	Spindle length mm	Height over spindle mm	Max output kW	Length mm	Weight kg	Air consumption at max output l/s	Air consumption at free speed l/s	Rec hose size mm	Air inlet thread BSP in	Ordering No.
LSV19 S200	20000	50	1/4"-20 UNC	8	59	0.46	186	0.6	11.3	7.5	10	1/4	8423 0111 42
LSV19 S120	12000	75	1/4"-20 UNC	8	59	0.46	186	0.6	11.3	7.5	10	1/4	8423 0111 44
LSV19 S080	8000	75	1/4"-20 UNC	8	59	0.37	186	0.6	11.3	6.5	10	1/4	8423 0111 45

Accessories

	8423 0111 42	8423 0111 44	8423 0111 45	Ordering No.
Included				
Open-end spanner (A/F 9mm)	✓	✓	✓	0902 0409 00
Hose (Soft type, Ø38, L = 1 m)	✓	✓	✓	4150 1314 02
Optional				
Hose kit (Cablair 10; 10 mm, L = 0.7 m)	✓	✓	✓	8202 1180 19
Syringe, filled with grease (RHENUS LKR03, 20 ml)	✓	✓	✓	4081 0530 90
MULTIFLEX-1/4 cover	✓	✓	✓	8202 1350 41
MULTIFLEX-1/4-NPT (For North America)	✓	✓	✓	8202 1350 26
MULTIFLEX-1/4	✓	✓	✓	8202 1350 20
Productivity kit (MIDI-FRL-1/2-BSP EQ08-C10)	✓	✓	✓	8202 0850 03