



Model	Max free speed r/min	Max pad dia mm	Spindle thread	Spindle length mm	Height over spindle mm	Max output kW	Length mm	Weight kg	Air consumption at max output l/s	Air consumption at free speed l/s	Rec hose size mm	Air inlet thread BSP in	Ordering No.
LSV28 S040-01-M14 (wet sanding)	4000	180	M14	23	104	0.62	268	1.5	15.0	4.0	10	3/8	8423 0125 12
LSV28 ST013-M14-LF	1300	180	M14	23	86	0.68	289	1.7	20.0	9.0	10	3/8	8423 0125 28
LSV28 ST008-01-LF (wet sanding)	800	200	5/8"-11 UNC	32	105	0.68	307	2.0	16.0	5.6	10	3/8	8423 0125 51

Accessories

	8423 0125 12	8423 0125 28	8423 0125 51	Ordering No.
Included				
Open-end spanner (A/F 17mm)	✓	✓	-	0902 0417 00
Open-end spanner (A/F 18mm)		✓	✓	4080 0729 00
Hose (Soft type, Ø38, L = 1 m)	✓	✓	✓	4150 1314 02
Allen key (6mm)	✓	✓	✓	4080 0048 00
Optional				
Hose kit (Cablair 10; 10 mm, L = 0.9 m)	✓	✓	✓	4150 1617 80
Syringe, filled with grease (RHENUS LKR03, 20 ml)	✓	✓	✓	4081 0530 90
Backing set, standard type (Ø125 mm - 5/8" - soft)	-	-	✓	4170 0768 80
Backing set, standard type (Ø180 mm - 5/8" - soft)	-	-	✓	4170 0756 80
Backing set, standard type (Ø180 mm - 5/8" - stiff)	-	-	✓	4170 0757 80
Backing set with cooling ribs (Ø125 mm - 5/8" and M14, medium)	✓	✓	✓	4150 1962 80
Backing set with cooling ribs (Ø180 mm - 5/8" and M14, medium)	✓	✓	✓	4150 1962 81
MULTIFLEX-3/8 cover	✓	✓	✓	8202 1350 42
MULTIFLEX-3/8-NPT (For North America)	✓	✓	✓	8202 1350 28
MULTIFLEX-3/8	✓	✓	✓	8202 1350 22