



Model	Max free speed r/min	Spindle thread	Max output kW	Max wheel dia mm	Length mm	Weight kg	Air consumption at max output l/s	Air consumption at free speed l/s	Rec hose size mm	Air inlet thread BSP in	Ordering No.
LSV29 S060-180	6000	5/8"-11 UNC	0.8	180	268	2.5	20	7	13	3/8	8423 0127 39
LSV29 ST12-100	12000	3/8"-24 UNF	0.8	100	248	1.7	20	8	10	3/8	8423 0127 45
LSV29 ST12-115	12000	3/8"-24 UNF	0.8	115	248	1.7	20	8	10	3/8	8423 0127 46
LSV29 ST12-125	12000	3/8"-24 UNF	0.8	125	248	1.7	20	8	10	3/8	8423 0127 47
LSV29 ST13-100E	13000	3/8"-24 UNF	0.8	100	300	1.7	26	15	10	3/8	8423 0127 49

Accessories

	8423 0127 39	8423 0127 45	8423 0127 46	8423 0127 47	8423 0127 49	Ordering No.
Included						
Open-end spanner (A/F 18mm)	-	✓	✓	✓	-	4080 0729 00
Face spanner (30 x Ø6 mm)	✓	-	✓	✓	-	4080 0862 00
Face spanner (26 x Ø4 mm)	-	✓	-	-	-	4080 0210 00
Allen key (6mm)	✓	-	-	-	-	4080 0048 00
Hose (Soft type, Ø38, L = 1 m)	✓	✓	✓	✓	✓	4150 1314 02
Flange washer complete	-	-	✓	✓	-	4150 1160 80
Optional						
Hose kit (Cablaire 10; 10 mm, L = 0.9 m)	✓	-	-	-	-	4150 1617 80
Hose kit (Turbo 13; 13 mm, L = 0.9 m)	-	✓	✓	✓	✓	8202 1181 98
Grease gun (0.8oz - 24gr)	-	-	-	-	✓	4150 1982 20
Syringe, filled with grease (RHENUS LKR03, 20 ml)	✓	✓	✓	✓	-	4081 0530 90
Diamond cutting wheel - Ø100 mm	-	✓	✓	✓	✓	3780 5074 00
Adds on spot suction - Ø115-150 mm	-	-	✓	✓	-	3780 4032 14
MULTIFLEX-3/8 cover	✓	✓	✓	✓	✓	8202 1350 42
MULTIFLEX-3/8-NPT (For North America)	✓	✓	✓	✓	✓	8202 1350 28
MULTIFLEX-3/8	✓	✓	✓	✓	✓	8202 1350 22