



Model	Max free speed r/min	Max pad dia mm	Spindle thread	Spindle length mm	Height over spindle mm	Max output kW	Length mm	Weight kg	Air consumption at max output l/s	Air consumption at free speed l/s	Rec hose size mm	Air inlet thread BSP in	Ordering No.
LSV29 S060-5/8	6000	180	5/8"-11 UNC	32	86	0.8	268	1.5	20	7	13	3/8	8423 0127 37
LSV29 S060-M14	6000	180	M14	23	86	0.8	266	1.5	20	7	13	3/8	8423 0127 50
LSV29 S018-5/8 (wet sanding)	1800	180	5/8"-11 UNC	32	104	0.8	290	1.7	22	13	13	3/8	8423 0127 52

Accessories

	8423 0127 37	8423 0127 50	8423 0127 52	Ordering No.
Included				
Open-end spanner (A/F 18mm)	✓	-	✓	4080 0729 00
Open-end spanner (A/F 17mm)	-	✓	-	0902 0417 00
Allen key (6mm)	✓	✓	✓	4080 0048 00
Hose (Soft type, Ø38, L = 1 m)	✓	✓	✓	4150 1314 02
Optional				
Hose kit (Cablaire 10; 10 mm, L = 0.9 m)	✓	✓	✓	4150 1617 80
Syringe, filled with grease (RHENUS LKR03, 20 ml)	✓	✓	✓	4081 0530 90
Backing set, standard type (Ø125 mm - 5/8" - soft)	✓	-	✓	4170 0768 80
Backing set, standard type (Ø180 mm - 5/8" - soft)	✓	-	✓	4170 0756 80
Backing set, standard type (Ø180 mm - 5/8" - stiff)	✓	-	✓	4170 0757 80
Backing set with cooling ribs (Ø125 mm - 5/8" and M14, medium)	✓	✓	✓	4150 1962 80
Backing set with cooling ribs (Ø180 mm - 5/8" and M14, medium)	✓	✓	✓	4150 1962 81
MULTIFLEX-3/8 cover	✓	✓	✓	8202 1350 42
MULTIFLEX-3/8-NPT (For North America)	✓	✓	✓	8202 1350 28
MULTIFLEX-3/8	✓	✓	✓	8202 1350 22
Productivity kit (MIDI-FRL-1/2-BSP EQ10-T13)	✓	✓	✓	8202 0850 17