



Model	Max free speed r/min	Max pad dia mm	Spindle thread	Spindle length mm	Height over spindle mm	Max output kW	Weight kg	Air consumption at max output l/s	Air consumption at free speed l/s	Rec hose size mm	Air inlet thread BSP in	Ordering No.
LSV29 S021-M14	2100	180	M14	23	86	0.7	1.9	19	6	13	3/8	8423 0127 34
LSV29 S040-5/8	4000	180	5/8"-11 UNC	32	86	0.7	1.5	19	6	13	3/8	8423 0127 35
LSV29 S013-5/8	1300	180	5/8"-11 UNC	32	86	0.7	1.7	25	9	13	3/8	8423 0127 42
LSV29 S034-5/8	3400	180	5/8"-11 UNC	32	86	0.8	1.7	21	8	13	3/8	8423 0127 44

Accessories

	8423 0127 34	8423 0127 35	8423 0127 42	8423 0127 44	Ordering No.
Included					
Open-end spanner (A/F 18mm)	-	✓	✓	✓	4080 0729 00
Open-end spanner (A/F 17mm)	✓	-	-	-	0902 0417 00
Allen key (6mm)	✓	✓	✓	✓	4080 0048 00
Hose (Soft type, Ø38, L = 1 m)	✓	✓	✓	✓	4150 1314 02
Optional					
Hose kit (Cablair 10; 10 mm, L = 0.9 m)	✓	✓	✓	✓	4150 1617 80
Syringe, filled with grease (RHENUS LKR03, 20 ml)	✓	✓	✓	✓	4081 0530 90
Ø150 mm Velcro pad, thread UNC 5/8" - Max speed 2500 rpm (To be used together with Velcro sponge heads or Velcro lambswool bonnet)	-	✓	✓	✓	4112 6092 15
Ø150 mm lambswool bonnet with Velcro fitting (Max speed 2500 rpm)	-	✓	✓	✓	4112 6093 15
Ø150 mm Velcro sponge head (Max speed 2500 rpm) - White, Dense, firm sponge head for compounding 2-pack paint systems. Excellent result with all leading makes of compound and polish.	-	✓	✓	✓	4112 6094 15
Threaded pads - Ø150 mm white sponge head pad UNC 5/8" (Max speed 4000 rpm)	-	✓	✓	✓	4112 6100 15