



Model	Max free speed r/min	Max pad dia mm	Spindle thread	Spindle length mm	Height over spindle mm	Max output kW	Length mm	Weight kg	Air consumption at max output l/s	Air consumption at free speed l/s	Rec hose size mm	Air inlet thread BSP in	Ordering No.
LSV39 S085-5/8	8500	180	5/8"-11 UNC	28	96	1.8	231	1.6	29.5	16.3	13	3/8	8423 0133 03
LSV39 S085-M14	8500	180	M14	28	96	1.8	231	1.6	29.5	16.3	13	3/8	8423 0133 04
LSV39 S066-5/8	6600	180	5/8"-11 UNC	28	96	1.6	231	1.6	26.2	11.6	13	3/8	8423 0133 05
LSV39 S066-M14	6600	180	M14	28	96	1.6	231	1.6	26.2	11.6	13	3/8	8423 0133 06
LSV39 S120-5/8	12000	125	5/8"-11 UNC	28	96	1.8	231	1.6	29.8	17.6	13	3/8	8423 0133 07
LSV39 S085-M14 S	8500	180	M14	19	96	1.8	231	1.6	29.5	16.3	13	3/8	8423 0133 11

Accessories

	8423 0133 03	8423 0133 04	8423 0133 05	8423 0133 06	8423 0133 07	8423 0133 11	Ordering No.
Included							
Allen key (4mm)	✓	✓	✓	✓	✓	✓	0902 0112 00
Hose (Soft type, Ø38, L = 1 m)	✓	✓	✓	✓	✓	✓	4150 1314 02
Looking kit	✓	✓	✓	✓	✓	✓	4170 1188 00
Optional							
Hose kit (Turbo 13; 13 mm, L = 0.9 m)	✓	✓	✓	✓	✓	✓	4150 1618 81
Syringe, filled with grease (RHENUS LKR03, 20 ml)	✓	✓	✓	✓	✓	✓	4081 0530 90
Backing set, standard type (Ø125 mm - 5/8" - soft)	✓	-	✓	-	✓	-	4170 0768 80
Backing set, standard type (Ø180 mm - 5/8" - soft)	✓	-	✓	-	-	-	4170 0756 80
Backing set, standard type (Ø180 mm - 5/8" - stiff)	✓	-	✓	-	-	-	4170 0757 80
Backing set with cooling ribs (Ø125 mm - 5/8" and M14, medium)	✓	✓	✓	✓	✓	✓	4150 1962 80
Backing set with cooling ribs (Ø180 mm - 5/8" and M14, stiff)	✓	✓	✓	✓	-	✓	4150 1962 83
Backing set with cooling ribs (Ø180 mm - 5/8" and M14, medium)	✓	✓	✓	✓	-	✓	4150 1962 81