

ETD STR

- Protected against intrusion of dust and water to withstand the toughest environments. IP class 54.
- Built in gyroscope to detect operators influence on tightening.
- Modular STR design for parts commonality between models and sizes.
- Dual accessories support for customizable functionality such as QR code scanning,
- EHMI display or headlights.
- High cycle rate capability due to improved heat dissipation.
- Operator feed back through built in loudspeaker, vibrator and high visibility LEDs.



ETD STR

Model	Square drive In	Torque range		Speed r/min	Weight		Length mm	CS distance mm	Ordering No.
		Nm	ft lb		kg	lb			
ETD STR31									
ETD STR31-05-10	3/8	1-5	0.7-3.6	3645	1.0	2.2	388	24	8436 6230 05
ETD STR31-10-10	3/8	2-10	1.4-7.3	1555	1.2	2.6	388	24	8436 6230 10
ETD STR31FemaleHex									
ETD STR31-05-I06-QC	1/4	1-5	0.7-3.6	3645	1.0	2.2	350	24	8436 6230 07
ETD STR31 Telescopic									
ETD STR31-05-10-T25	3/8	1.5-5	1.1-3.7	1310	1.1	2.4	437	11	8436 6230 06
ETD STR31-10-10-T25	3/8	2-10	1.4-7.3	1555	1.3	2.9	436.5	24	8436 6230 11
ETD STR61									
ETD STR61-15-10	3/8	4-16	3-12	2500	1.4	3.1	438	24	8436 6260 15
ETD STR61-20-10	3/8	5-22	3.6-16	1890	1.4	3.1	438	24	8436 6260 20
ETD STR61-30-10	3/8	6-35	4.4-25	1130	1.4	3.1	429	24	8436 6260 30
ETD STR61-50-13	1/2	10-55	7.3-40	819	2.0	4.4	474	24	8436 6260 50
ETD STR61-70-13	1/2	15-80	12-58	560	2.3	5.1	491	26.5	8436 6260 70
ETD STR61-90-13	1/2	20-95	15-70	440	2.3	5.1	491	26.5	8436 6260 90
ETD STR61 Female Hex									
ETD STR61-15-I06-QC	1/4	4-16	3-12	2500	1.3	2.9	429	24	8436 6260 18
ETD STR61 Telescopic									
ETD STR61-15-10-T25	3/8	4-16	3-12	2500	1.5	3.3	477	24	8436 6260 16
ETD STR61-15-10-T50	3/8	4-16	3-12	2500	1.6	3.5	527	24	8436 6260 17
ETD STR61-20-10-T25	3/8	5-22	3.6-16	1890	1.5	3.3	477	24	8436 6260 21
ETD STR61-30-10-T25	3/8	6-35	4.4-25	1130	1.5	3.3	468	24	8436 6260 31
ETD STR61-30-10-T50	3/8	6-35	4.4-25	1130	1.5	3.3	518	24	8436 6260 32
ETD STR61-50-13-T25	1/2	10-55	7.3-40	819	2.2	4.8	501	24	8436 6260 51
ETD STR61-50-13-T50	1/2	10-55	7.3-40	819	2.1	4.6	557	24	8436 6260 52
ETD STR61-70-13-T25	1/2	15-60	12-58	560	2.4	5.4	518	24	8436 6260 71
ETD STR61-90-13-T25	1/2	20-95	15-70	440	2.4	5.4	518	24	8436 6260 91
ETD STR61-120-13-T50	1/2	36-120	26-88	495	2.5	5.5	574	26.5	8436 6260 62