

ETP ST REVO

ETP ST REVO

- Unique and patented 360 deg swivel with transducer.
- Ultra-compact size improves access.
- Reduced weight means less need for fixtures.
- Display on tool gives direct feedback of tightening result.
- Program selection is made directly on tool.
- Ideal for handheld application or fixtures with reduced space.
- Torque range from 60-8000 Nm.



ETP ST REVO

Model	Square drive	Torque range		Speed	Weight		Length	Height	Spline	Ordering No.
	In	Nm	ft lb	r/min	kg	lb	mm	mm		
Model with fan										
ETP ST101-200-20-F	3/4	60-200	45-145	396	5.2	11.5	303	32.5	3	8433 2302 02
ETP ST101-300-20-F	3/4	90-300	66-221	293	5.2	11.5	303	32.5	3	8433 2303 02
ETP ST101-500-20-F	3/4	150-500	110-365	186	5.9	13	334	33.5	4	8433 2305 02
ETP ST101-750-25-F	1	220-750	160-550	132	6.2	13.7	353	33.5	5	8433 2307 52
ETP ST101-1000-25-F	1	300-1000	220-735	99	6.4	14.1	364	33.5	5	8433 2310 02
ETP ST101-1500-25-F	1	450-1500	332-1106	47	8.8	19.4	402	43.5	9	8433 2321 52
ETP ST101-2000-38-F	1 1/2	600-2000	442-1475	38	11.5	25.4	454	48	7	8433 2322 02
ETP ST101-3000-38-F	1 1/2	900-3000	664-2212	24	14.8	33	476	59	8	8433 2323 02
ETP ST101-4000-38-F	1 1/2	1200-4000	885-2950	20	15	33	481	59	8	8433 2324 02
ETP ST101-1300-20-F-HA	3/4	390-1300	288-1000	65	6.4	14.1	348	32	–	8433 2313 03
ETP ST101-2400-25-F-HA	1	720-2400	532-1770	31	7.5	16.5	400	35.5	–	8433 2326 03
ETP ST101-4000-25-F-HA	1	1200-4000	885-2950	16	11	24.2	461	50.5	–	8433 2324 03
ETP ST101-5500-38-F-HA	1 1/2	1650-5500	1217-4056	17	13.2	29.1	452	53	–	8433 2325 03
ETP ST101-6500-38-F-HA	1 1/2	1950-6500	1440-4800	12	13.2	29.1	452	53	–	8433 2327 03
ETP ST101-8000-38-F-HA	1 1/2	2400-8000	1770-5900	10	13.2	29.1	452	53	–	8433 2328 03

Reaction bar not included for ETP ST101. See accessory pages.