

TBP - S

TBP - S

TBP - S is a low reaction tool with maximum flexibility and high torque. Thanks to the DuraPulse technology the tool uptime is increased and keeps it on the line instead of the tool crib. With TorqueBoost, active cooling and advanced motor steering, the torque build up is fast with reduced hours per production unit and the tool has high productivity. TBP - S is suitable for Quality Critical joints and will report OK/NOK to MES-system.

- DuraPulse technology with new sealing and air separator.
- High torque.
- Excellent ergonomics with low vibrations and reaction force.
- Cooling system to prevent the tool from over-heating.
- Buffer battery.
- Dual antenna.
- Rapid Backup Unit (RBU) functionality.
- LED indicators to provide operator feedback.
- Natural step in transformation from air pulse tools.
- Can be run as stand-alone tool.



TBP - S

Model	Square drive	Torque range		Battery	Speed	Weight	Weight incl battery	Length	CS distance	Ordering No.
	In	Nm	ft lb		r/min	kg	kg	mm	mm	
Transducerized Tensor TBP - S										
ETP TBPS61-32-10	3/8	12-35	8.9-25.8	18 V	6000	1.330	1.835	195	231	8433 3230 25
ETP TBPS61-32-42	1/4	12-35	8.9-25.8	18 V	6000	1.330	1.835	195	231	8433 3230 27
ETP TBPS81-55-10	3/8	20-55	14.8-40.6	18 V	6000	1.5	2.0	200	231	8433 3230 35
ETP TBPS91-80-13	1/2	40-80	29.5-59.0	18/36 V	6000	1.8	2.6	210	231	8433 3230 45
ETP TBPS131-150-13	1/2	55-150	41-111	36 V	3600	2.80	3.50	227	255	8433 3230 65