

High Performance “Angle Drill”

The **AVRO CF120 & CF125** series of Angle drills are High Performance tools designed for the most demanding requirements of the 21st century applications.

Incorporating the latest **ERGONOMIC** principles into the design, your productivity is our primary goal. The **HIGH POWER-TO-WEIGHT** ratio and complete throttle control mean the shortest possible completion on all operations.

General:

- Air Inlet: 1/4" NPT Standard
- Use 5/16" (8mm) I.D Hose
- Air pressure 90 psi (620 KPA)

Model	Speed	Spindle	Length	Weight
	Rpm	Inch	Inch / mm	Lbs / kg

Cf120 0.6 hp (450w) Rear Exhaust

23001	4,500	3/8-24	10" / 254	2.1 / 0.95
23002	3,400	3/8-24	10" / 254	2.1 / 0.95
23003	2,200	3/8-24	11.8" / 299	2.4 / 1.08
23004	1,100	3/8-24	11.8" / 299	2.4 / 1.08
23005	700	3/8-24	11.8" / 299	2.4 / 1.08

Cf125 1.0 hp (745w) Rear Exhaust

24001	1,600	1/2-20	12.6" / 320	3.3 / 1.48
24002	1,200	1/2-20	12.6" / 320	3.3 / 1.48
24003	500	1/2-20	13.8" / 350	3.7 / 1.68

Optional Chucks:

Add following suffix to part number
e.g: **24001F** = 1600 RPM 1/4" Keyless

A = 1/4" (6.3mm) Standard Duty 1B
B = 1/4" (6.3mm) Heavy Duty 7B
C = 3/8" (9.5mm) Standard Duty 41B
D = 3/8" (9.5mm) Heavy Duty 2B
E = 1/2" (12.7mm) Heavy Duty 33B

F = 1/4" (6.3mm) Keyless
G = 3/8" (9.5mm) Keyless
J = No Chuck



4175 boul. Poirier
Montréal, Québec, Canada H4R 2G9
T: 514-336-9444 | 1-866-874-9444
F: 514-336-0277 | 1-888-336-6055
info@avrotools.com