

Avro Rivet Shaver

Avro "Raptor" Rivet Shaver

Avro's lightweight **rivet shaver** has been designed for ultimate precision and consistency. Cutter adjustment is 0.00042" (0.010668mm) increment.



General:

- Air Inlet: 1/4" NPT Standard
- Use 5/16" (8mm) I.D Hose
- Air pressure 90 psi (620 KPA)

"Raptor" XT255RS .5HP(0.37KW) 20,000RPM

Model	Skirt	RPM	Adjustmen	Length	Weight
14115AA	1/4" (6.3mm)	20,000	0.00042"	8.25" (209mm)	1.5lbs (0.69kg)
14115A	5/16" (8mm)	20,000	0.00042"	8.25" (209mm)	1.5lbs (0.69kg)
14115B	3/8" (10mm)	20,000	0.00042"	8.25" (209mm)	1.5lbs (0.69kg)
14115C	7/16" (11mm)	20,000	0.00042"	8.25" (209mm)	1.5lbs (0.69kg)
14115D	1/2" (13mm)	20,000	0.00042"	8.25" (209mm)	1.5lbs (0.69kg)
14115E	9/16" (14mm)	20,000	0.00042"	8.25" (209mm)	1.5lbs (0.69kg)
14115F	5/8" (16mm)	20,000	0.00042"	8.25" (209mm)	1.5lbs (0.69kg)

Rivet Shaver Skirts and Cutters

Skirt Diameter	1/4" (6.3mm)	5/16" (8mm)	3/8" (10mm)	7/16" (11mm)	1/2" (13mm)	9/16" (14mm)	5/8" (16mm)
Stainless	A28000	A28001	A28002	A28003	A28004	A28005	A28006

Stabilizer Kit is not included with the tool



4175 boul. Poirier
Montréal, Québec, Canada H4R 2G9
T: 514-336-9444 | 1-866-874-9444
F: 514-336-0277 | 1-888-336-6055
info@avrotools.com

D

avrotools.com