

Single Cylinder "Alligator" Squeezers

Avro offers a diverse selection of rivet squeezers for today's demanding applications. Special jaws or yokes are available upon request. All Avro riveters are available with high output wedges for high force applications. A micrometer style adjustable set holder is available on all rivet squeezers to eliminate the use of shims.



Model Number	Capacity	Force	Reach	G A P	Max Travel	Length	Weight
	Alum / Steel	PSI	Inch / mm		Inch / mm	Inch / m	lbs / kg
10158	1/8" / 3/32"	3000	1.5" / 38.1	7/8"	5/8" / 15.8	9-1/4" / 235	4 / 1.8
10159	3/32" / 3/32"	2400	2.25" / 50.8	7/8"	7/8" / 22.2	10" / 254	4.5 / 2.04
10160	3/32" / 1/16"	1800	3" / 76.2	7/8"	1-1/4" / 21.75	10-3/4" / 273	5 / 2.25
10158HD	5/32" / 1/8"	3900	1.5" / 38.1	7/8"	5/8" / 15.8	9-1/4" / 235	4 / 1.8
10159HD	1/8" / 3/32"	3000	2.25" / 50.8	7/8"	7/8" / 22.2	10" / 254	4.5 / 2.04
10160HD	3/32" / 1/16"	2400	3" / 76.2	7/8"	1-1/4" / 21.75	10-3/4" / 273	5 / 2.25

- Adjustable set holder available for all Yokes. Specify "ADJ". (Example: 10158ADJ)
- 5mm set holders are available upon request. Specify "E". (Example: 10158E)
- Other size + custom yokes available upon request.

General:

- All specifications are rated at 90PSI (6.21 BAR) air pressure.
- Air Inlet 1/4 NPT Standard.
- Use 5/16(8 mm) ID Hose.

