

Single Cylinder "C" Yoke Squeezers

Avro offers a diverse selection of rivet squeezers for today's demanding applications. Special jaws or yokes are available upon request. All Avro riveters are available with high output wedges for high force applications. A micrometer style adjustable set holder is available on all rivet squeezers to eliminate the use of shims.



Model Number	Capacity	Force	Reach	G A P	Max Travel	Length	Weight
	Alum / Steel	PSI	Inch / mm		Inch / mm	Inch / m	lbs / kg
10150	1/8" / 3/32"	3000	1.5" / 38.1	1.25"	9/16 / 14.27	10-1/4 / 260.4	4.5 / 2.04
10151	1/8" / 3/32"	3000	2" / 50.8	1.25"	9/16 / 14.27	10-1/4 / 260.4	5 / 2.3
10152	1/8" / 3/32"	3000	2.5" / 63.5	1.25"	9/16 / 14.27	11 / 279.4	5.5 / 2.9
10153	1/8" / 3/32"	3000	3" / 76.2	1.25"	9/16 / 14.27	11-1/4 / 286	6 / 2.72
10150HD	5/32" / 3/32"	3800	1.5" / 38.1	1.25"	9/16 / 14.27	10-1/4 / 260.4	4.5 / 2.04
10151HD	5/32" / 3/32"	3800	2" / 50.8	1.25"	9/16 / 14.27	10-1/4 / 260.4	5 / 2.3
10152HD	5/32" / 3/32"	3800	2.5" / 63.5	1.25"	9/16 / 14.27	11 / 279.4	5.5 / 2.9
10153HD	5/32" / 3/32"	3800	3" / 76.2	1.25"	9/16 / 14.27	11-1/4 / 286	6 / 2.72

- Adjustable set holder available for all Yokes. Specify "ADJ". (Example: 10150ADJ)
- 5mm set holders are available upon request. Specify "E". (Example: 10150E)
- Other size + custom yokes available upon request.

General:

- All specifications are rated at 90PSI (6.21 BAR) air pressure.
- Air Inlet 1/4 NPT Standard.
- Use 5/16(8 mm) ID Hose.

