

Tandem Cylinder "Alligator" Squeezers

Avro offers a diverse selection of rivet squeezers for today's demanding applications. Special jaws or yokes are available upon request. All Avro riveters are available with high output wedges for high force applications. A micrometer style adjustable set holder is available on all rivet squeezers to eliminate the use of shims.



Model Number	Capacity	Force	Reach	G A P	Max Travel	Length	Weight
	Alum / Steel	PSI	Inch / mm		Inch / mm	Inch / m	lbs / kg
10161	3/16" / 532"	6000	1.5" / 38.1	7/8"	5/8" / 15.8	12" / 304.8	5.5 / 2.5
10162	3/16" / 1/8"	4600	2.25" / 50.8	7/8"	7/8" / 22.2	12-3/4" / 324	5.5 / 2.5
10163	5/32" / 3/32"	3400	3" / 76.2	7/8"	1-1/4" / 21.75	13-1/2" / 343	6 / 2.72
10161HD	3/16" / 532	7200	1.5" / 38.1	7/8"	5/8" / 15.8	12" / 304.8	5.5 / 2.5
10162HD	3/16" / 1/8"	5300	2.25" / 50.8	7/8"	7/8" / 22.2	12-3/4" / 324	5.5 / 2.5
10163HD	5/32" / 1/8"	4000	3" / 76.2	7/8"	1-1/4" / 21.75	13-1/2" / 343	6 / 2.72

- Adjustable set holder available for all Yokes. Specify "ADJ". (Example: 10161ADJ)
- 5mm set holders are available upon request. Specify "E". (Example: 10161E)
- Other size + custom yokes available upon request.

General:

- All specifications are rated at 90PSI (6.21 BAR) air pressure.
- Air Inlet 1/4 NPT Standard.
- Use 5/16(8 mm) ID Hose.

