

Tandem Cylinder "C" Yoke Squeezers

Avro offers a diverse selection of rivet squeezers for today's demanding applications. Special jaws or yokes are available upon request. All Avro riveters are available with high output wedges for high force applications. A micrometer style adjustable set holder is available on all rivet squeezers to eliminate the use of shims.



Model Number	Capacity	Force	Reach	G A P	Max Travel	Length	Weight
	Alum / Steel	PSI	Inch / mm		Inch / mm	Inch / m	lbs / kg
10154	3/16" / 5/32"	6000	1.5" / 38.1	1.25"	9/16" / 14.2	14" / 356	5.5 / 2.5
10155	3/16" / 5/32"	6000	2" / 50.8	1.25"	9/16" / 14.27	14-1/2" / 368	6 / 2.72
10156	3/16" / 5/32"	6000	2.5" / 63.5	1.25"	9/16" / 14.27	14-3/4" / 374	6.5 / 3
10157	3/16" / 5/32"	6000	3" / 76.2	1.25"	9/16" / 14.27	15" / 281	7 / 3.2
10154HD	3/16" / 5/32"	7600	1.5" / 38.1	1.25"	9/16" / 14.2	14" / 356	5.5 / 2.5
10155HD	3/16" / 5/32"	7600	2" / 50.8	1.25"	9/16" / 14.27	14-1/2" / 368	6 / 2.72
10156HD	3/16" / 5/32"	7600	2.5" / 63.5	1.25"	9/16" / 14.27	14-3/4" / 374	6.5 / 3
10157HD	3/16" / 5/32"	7600	3" / 76.2	1.25"	9/16" / 14.27	15" / 281	7 / 3.2

- Adjustable set holder available for all Yokes. Specify "ADJ". (Example: 10154ADJ)
- 5mm set holders are available upon request. Specify "E". (Example: 10154E)
- Other size + custom yokes available upon request.

General:

- All specifications are rated at 90PSI (6.21 BAR) air pressure.
- Air Inlet 1/4 NPT Standard.
- Use 5/16(8 mm) ID Hose.

