

Triple Cylinder "Alligator" Squeezers

Avro offers a diverse selection of rivet squeezers for today's demanding applications. Special jaws or yokes are available upon request. All Avro riveters are available with high output wedges for high force applications. A micrometer style adjustable set holder is available on all rivet squeezers to eliminate the use of shims.



Model Number	Capacity	Force	Reach	G A P	Max Travel	Length	Weight
	Alum / Steel	PSI	Inch / m		Inch / mm	Inch / m	lbs / kg
10165	1/4" / 3/16"	9000	1.5" / 38.1	7/8"	5/8" / 15.8	16" / 406.4	7 / 3.17
10166	3/16" / 5/32"	7000	2.25" / 50.8	7/8"	7/8" / 22.2	16.75" / 425.4	7.5 / 3.4
10167	3/16" / 5/32"	5200	3" / 76.2	7/8"	1-1/4" / 21.7	17-1/4" / 444.5	8 / 3.62
10170	3/16" / 5/32"	5200	5" / 127	7/8"	1-1/4" / 21.75	17-1/4" / 444.5	8 / 3.62
10180	9/32" / 7/32"	10900	3" / 76.2	7/8"	1-3/16" / 30.16	19-3/4" / 501.6	11.5 / 5.2
10181	1/4" / 3/16"	5900	5" / 127	7/8"	1-3/8" / 35	21-3/4" / 552.4	12 / 5.44
10182	3/16" / 1/8"	4700	7" / 178	7/8"	1-13/16" / 46	23-3/4" / 603.2	12-5 / 5.7

- Adjustable set holder available for all Yokes. Specify "ADJ". (Example: 10165ADJ)
- 5mm set holders are available upon request. Specify "E". (Example: 10165E)
- Other size + custom yokes available upon request.

General:

- All specifications are rated at 90PSI (6.21 BAR) air pressure.
- Air Inlet 1/4 NPT Standard.
- Use 5/16(8 mm) ID Hose.

