

Avro Rivet Guns

Rivet Hammer & Wolf Pack: " 2X 3X 4X "



The **AVRO** series of **Riveting Hammers** features an "ERGONOMIC" housing design for maximum operator comfort. The comfort "ERGO GRIP" acts as a thermal protector and isolates vibrations. A spool valve system delivers slow, heavy blows necessary to drive rivets. An extremely sensitive teasing throttle permits precise control.

General:

- Air Inlet: 1/4" NPT Standard
- Air pressure: 90 psi (620 kpa).
- Shank Diameter .401"

Model Number		Capacity	Blows	Bore	Stroke	Length	Weight
		Alum / Steel	Minute	Inch / mm	Inch / mm	Inch / mm	lbs / kg
10020	2X	1/8" / 3/32"	2600	1/2" / 12.7	2-1/4 / 57.2	6-11/16 / 170	2.60 / 1.18
10030	3X	3/16" / 5/32"	2100	1/2" 12.7	2-7/8 / 73.0	7-5/16 / 185	2.80 / 1.27
10040	4X	1/4" / 3/16"	1700	1/2" 12.7	3-1/16 / 77.5	8-5/16 / 211	3.05 / 1.38



The Avro "**WOLFPACK**" series of riveting hammers feature a revolutionary Tungsten piston design that delivers far more power and assists in absorbing vibration, allowing the operator to choose a smaller and lighter tool for the same application.

Model Number		Capacity	Blows	Bore	Stroke	Length	Weight
		Alum / Steel	Minute	Inch / mm	Inch / mm	Inch / mm	lbs / kg
10025	2X	3/16" / 1/8"	2600	1/2" / 12.7	2-1/4 / 57.2	6-11/16 / 170	2.65 / 1.20
10035	3X	1/4" / 3/16"	2100	1/2" 12.7	2-7/8 / 73.0	7-5/16 / 185	2.90 / 1.32
10045	4X	5/16" / 1/4"	1700	1/2" 12.7	3-1/16 / 77.5	8-5/16 / 211	3.15 / 1.43



4175 boul. Poirier
Montréal, Québec, Canada H4R 2G9
T: 514-336-9444 | 1-866-874-9444
F: 514-336-0277 | 1-888-336-6055
info@avrotools.com

C

avrotools.com