

Avro "Pressure Foot Drill "



Avro's Pressure Foot Drill helps eliminate drill bushing wear in production tooling. Bushing life is extended considerably. The Pressure Foot nosepiece is threaded on the drill motor housing. This allows greater concentricity. The nosepiece can be adjusted backwards and forwards to accommodate different length drill bits as a result of sharpening.

Model Number		Free Speed	Chuck Capacity	Spindle Thread	Maximum Torque	Length	Weight
For .750"	For .687"	Rpm	In / mm	Inch	lb / Nm	Inch / mm	lbs / kg
15020PFD	15120PFD	20,000	1/4 / 6.35	3/8 -24	0.3 / 0.4	7.5 / 190	1.7 / 0.76
15022PFD	15122PFD	5,000	1/4 / 6.35	3/8 -24	1.3 / 1.7	7.5 / 190	1.7 / 0.76
15023PFD	15123PFD	3,200	1/4 / 6.35	3/8 -24	2.5 / 3.4	7.5 / 190	1.7 / 0.76
15024PFD	15124PFD	2,400	1/4 / 6.35	3/8 -24	3.3 / 4.5	7.5 / 190	1.7 / 0.76
15025PFD	15125PFD	1,600	1/4 / 6.35	3/8 -24	4.2 / 5.7	8.6 / 218	1.8 / 0.83
15026PFD	15126PFD	1,000	1/4 / 6.35	3/8 -24	5.5 / 7.5	8.6 / 218	1.8 / 0.83
15027PFD	15127PFD	800	1/4 / 6.35	3/8 -24	5.8 / 7.8	8.6 / 218	1.8 / 0.83
15028PFD	15128PFD	500	1/4 / 6.35	3/8 -24	7.5 / 10.2	8.6 / 218	1.8 / 0.83

***Pressure Foot Adapter & Drill Guide are not included

Vacuum Short	Vacuum Long
A90080	A90085

General:

- Power 0.5 hp (0.37 kw)
- Air Inlet: 1/4" NPT Standard
- Air pressure: 90 psi (620 kpa).



4175 boul. Poirier
Montréal, Québec, Canada H4R 2G9
T: 514-336-9444 | 1-866-874-9444
F: 514-336-0277 | 1-888-336-6055
info@avrotools.com