

GB947 & GB947-220 HYDRAULIC POWERUNIT

GAGE BILT

RIVET & LOCKBOLT TOOLS

44766 Centre Ct. Clinton Twp. MI 48038 USA

+1 586. 226.1500

+1 586. 226.1505


solutions@gagebilt.com

www.gagebilt.com

On / Off



Return Pressure Adjusting Screw




Loosen/Tighten Nut

Oil Reservoir



Loosen/Tighten Nut



Pull Pressure
Adjusting Knob

RETURN

PULL

Oil Drain

Oil Fill Level

Electrical Plug For Tool



Adjust Pull Pressure – Loosen nut, turn knob clockwise to increase pressure or counter clockwise to reduce pressure. Once correct pressure is achieved, tighten nut.

Adjust Return Pressure – Loosen nut, using a hex key turn screw clockwise to increase pressure or counter clockwise to reduce pressure. Once correct pressure is achieved, tighten nut.

Hydraulic Oil – Use DEXRON III® or equivalent. Fill reservoir to 2" below the top.

Motor Voltage – GB947 = 120VAC, 50/60HZ, 20 AMP Circuit.
– GB947-220 = 230VAC, 50/60HZ, 20 AMP Circuit

Oil Temperature Operating Range = 0° F - 176° F (-17.8° C - 80° C). (Temperature should not exceed 180° F (82.2° C)).

Width.....	10.5 inches.....	267 mm
Length.....	16.5 inches.....	419 mm
Height.....	17.9 inches.....	454 mm
Weight (without hyd. oil).....	52.0 pounds.....	23.6 kg
Weight (with hyd. oil).....	62.0 pounds.....	28.1 kg

DEXRON® is a registered trademark of General Motors Corporation.

1/23 REV 9/23

