


NOSE ASSEMBLY DATA SHEET



CAUTION:
Pintail may eject forcibly. Use for closed access applications only to prevent SEVERE PERSONAL INJURY!

ASSEMBLY INSTRUCTIONS:

On front of GBP204 installation tool remove screw and stop. With collet placed in housing, install on tool. Slide draw bar thru housing and collet. Using an allen wrench, tighten the nut on the end of the draw bar (apply wibr-tite part no. 405124 to threads on draw bar). Replace screw and stop on tool.

11/01

Covered Under Patent No. 5,371,933

* Use Adapter No. 352204

** Use Adapter No. 353204

*** Use Adapter No. 352204 with 713152 stroke limiter.

GAGE BILT

GAGE BILT PRODUCTS CORP.

14500 Barber Drive

(586) 771-7664

Warren, Mi 48088

(586) 771-2665 Fax

e-mail: solutions@gagebilt.com / www.gagebilt.com

Type:		Fasteners:		Recommended Tool:	
Non Self Releasing 1/8, 5/32, 3/16 Ø		MBC NAS 1719 NAS 1720 NAS 1721		GBP204	
				Alt. Tools: *GBP752B **GBP745B, ****GBP713	
Ref. No.	Qty.	Description	MBC04-204B-27OS	MBC05-204B-27OS	MBC06-204B-27OS
1	1	Anvil Insert	10259	10260	10261
2	1	Anvil Assembly	10992	10993	10994
2a		(Includes #1)			
3	1	Collet	20714	20714	20714
4	1	Maxi-Jaw Assembly	30425-S1	30545-S1	30656-S1
5	1	Cap	70647	70647	70647
6	1	Draw Bar	71116	71116	71116
7	1	Nut	71114	71114	71114