


NOSE ASSEMBLY DATA SHEET




ASSEMBLY:

Notes:

1. Thread nut (3) onto puller (2) as shown in dimensional view. *Note: Thread on puller (2) is a left hand thread.*
2. Thread assembled puller (2) in tool's end cap. *Note: Thread on puller (2) is a left hand thread.*
3. Collapse puller and tighten nut (3) using wrench part # 200160. (Shipped with tool).
4. Install anvil assy (1) over puller (2) and thread into tool's piston.
5. Tighten anvil assy using a spanner wrench.

DISASSEMBLY:


Reverse assembly instructions.



WARNING:

EXPOSED MOVING PARTS. KEEP HANDS OFF DURING OPERATION TO PREVENT PERSONAL INJURY.

1 APPLY LOCTITE® C5-A® ANTI-SIEZE LUBRICANT (408183) OR EQUIVALENT TO OUTSIDE OF PULLER AND INSIDE DIAMETER OF ANVIL.



1/23 REV 10/24



GAGE BILT
MADE in USA

44766 Centre Court, Clinton Twp., MI. 48038 USA
Ph: +1 (586) 226-1500 Fax: +1 (586) 226-1505
solutions1@gagebilt.com / www.gagebilt.com

Type:		Fasteners:		Recommended Tool: GB20SF
Self-Releasing 12mmØ		Bobtail® Lockbolt		
Ref. No.	Qty.	Description		BOB12MM- 20SF-10
1	1	Anvil Assembly		11277
2	1	Puller		31243
3	1	Nut		72007

BOBTAIL® IS A REGISTERED TRADEMARK OF HOWMET AEROSPACE. LOCTITE® AND C5-A® ARE REGISTERED TRADEMARKS OF HENKEL CORPORATION U.S.A.