


NOSE ASSEMBLY DATA SHEET




ASSEMBLY:

Notes:

- Apply Vibra-tite® p/n/ 405125 to all threads and allow it to set 20 minutes prior to assembly.
 - If nose assy is assembled as it is when purchased new, follow steps 2-4 to attach to tool.
- Insert super grip jaw assy (3) into rear of collet (2).
 - Thread collet (2) to piston on tool and tighten using flats provided and hex in rear of piston.
 - Slide anvil assembly (1) over collet (2).
 - Slide retaining nut stop and retaining nut over ears on anvil (see exploded view) and tighten to tool.

DISASSEMBLY:

Reverse assembly instructions.



11/15 Rev. 3/25



*Anvil Assembly includes 35208 retainer.
**Yellow band designates nose assemblies for lightweight GP® fasteners.

GAGE BILT
MADE in USA

44766 Centre Court Clinton Twp. MI 48038 USA
Ph: +1 (586) 226-1500 Fax: +1 (586) 226-1505
solutions1@gagebilt.com / www.gagebilt.com

Type:		Fasteners:	Recommended Tool:
Non Self-Releasing 3/16" Ø		LGP® Lockbolts ASNA2391-3 ASNA2392-3	GB731
			Alternate Tools: GB730 & GB2480(A)
Ref. No.	Qty.	Description	LGP06-2480-10
1	1	*Anvil Assembly	16621
2	1	Collet	20660
3	1	Super-Grip Jaw Assembly	30651-S2

GP® AND LGP® ARE REGISTERED TRADEMARKS OF HOWMET AEROSPACE. VIBRA-TITE® IS A REGISTERED TRADEMARK OF OAKLAND CORPORATION.