


NOSE ASSEMBLY DATA SHEET



ASSEMBLY:

Notes:


- Apply Vibra-tite® p/n/ 405125 to all threads and allow it to set 20 minutes prior to assembly.
- Tighten collet (3) and extension-collet (6) to 80 - 100 IN-LBS. (.36 - .44 Kn) torque.

C. If nose assy is assembled as it is when purchased new, follow steps 3 - 5 to attach to tool.

- Insert super grip jaw assy (4) into rear of collet (3). Place spacer (5) on rear of super grip jaw assy (4)
- Thread collet (3) to extension-collet (6) using hex key in front of collet-extension (6) and flats provided on collet (3).
- Thread assembled collet (3) and extension-collet (6) onto piston of tool using flats provided and hex in rear of piston.
- Slide anvil & holder assembly (2) over collet (3).
- Slide retaining nut stop and retaining nut over ears on anvil (see exploded view) and tighten to tool.

DISASSEMBLY:

Reverse assembly instructions.



*Anvil Assembly consists of #1 and 35208 retainer

12/18 REV 9/25

GAGE BILT
MADE in USA

44766 Centre Court Clinton Twp. MI 48038 USA
Ph: +1 (586) 226-1500 Fax: +1 (586) 226-1505
solutions1@gagebilt.com / www.gagebilt.com

Type:		Fastener:	Recommended Tool:
Non Self-Releasing 8mm Ø		AVSEAL® Engine Plug	GB751
			Alternate Tools: GB722, GB752 & GB2480(A)
Ref. No.	Qty.	Description	8AVP2-752C-20
1	1	Anvil-Driving	16029-1
2	1	Anvil & Holder Assembly (Inc. #1)	11334
3	1	Collet	20727
4	1	Super-Grip Jaw Assembly	30656-CS
5	1	Spacer	70572
6	1	Extension-Collet	70550

AVSEAL® IS A REGISTERED TRADEMARK OF AVDEL U.K. LTD. VIBRA-TITE® IS A REGISTERED TRADEMARK OF OAKLAND CORPORATION.