


NOSE ASSEMBLY DATA SHEET



ASSEMBLY:

Notes:

- Apply Vibra-tite® p/n/ 405125 to all thread and allow it to set 20 minutes prior to assembly.
 - Tighten collet assy (2) and extension-collet (7) to 80-100 IN-LB torque.
 - If nose assy is assembled as it is when purchased new, follow steps 5-6 to attach to tool.
- Place extension-collet (7) on a table with threads facing upward.
 - Slide spring (5) over sleeve (6) then place follower (4) onto opposite end of spring (5).
 - Stack assembled follower (4), spring (5) and sleeve (6) onto standing extension-collet (7).
Place jaw set (3) onto top of follower (4). (See exploded view).
 - Slide collet assy (2) over stacked assembly and hand tighten. Tighten assembled collet (2) to extension-collet (7) using flats provided per note "B" above and hex key in front of extension.
 - Thread assembled collet (2) and extension-collet (7) to piston on tool using flats provided and hex key in rear of piston on tool.
 - Slide retaining nut over ears on anvil (1) **(Note: retaining nut stop not used on self releasing nose assemblies)** and tighten to tool.

DISASSEMBLY:

Reverse assembly instructions.

11/20 REV 3/25

*Anvil Assembly includes 35208 retainer.

GAGE BILT
MADE in USA

44766 Centre Court Clinton Twp. MI 48038 USA
Ph: +1 (586) 226-1500 Fax: +1 (586) 226-1505
solutions1@gagebilt.com / www.gagebilt.com

Type:		Fasteners:	Recommended Tool: GB731
Self-Releasing 3/16"Ø		NAS Shear and Tension Pull Type Lockbolts, C6L® and GP® Lockbolts	Alternate Tools: GB730 & GB2480(A)
Ref. No.	Qty.	Description	NAS06-352C-20
1	1	Anvil Assembly	16601
2	1	Collet Assy (Includes #8)	26610
3	1	Chuck Jaw Set	30654-1
4	1	Follower	40643
5	1	Spring	50621
6	1	Sleeve	60614
7	1	Extension-Collet	70636
8	1	Release & Ejector	80620

C6L® AND GP® ARE REGISTERED TRADEMARKS OF HOWMET AEROSPACE. VIBRA-TITE® IS A REGISTERED TRADEMARK OF OAKLAND CORPORATION.