


NOSE ASSEMBLY DATA SHEET



ASSEMBLY:

Notes:

- A. Tighten puller (4) and extension-Puller (5) to 80-100 IN-LB torque.
 B. If nose assy is assembled as it is when purchased new, follow steps 2-7 to attach to tool.

1. Thread nut (4) onto rear of puller (3) as shown in exploded view.
2. Thread extension-puller (5) into piston of tool.
3. Thread puller (4) into extension-puller (5).
Note: Thread on puller (4) is a left hand thread.
4. Tighten nut (3) against face of extension-puller (5) using wrench provided with GB20SF tool.
Note: Thread on puller (4) is a left hand thread.
5. Thread anvil (1) onto anvil holder (2).
6. Thread assembled anvil holder (1 & 2) onto tool aligning groove on anvil holder (2) with the 3 set screws on the tool.
7. Tighten the 3 set screws on the tool locking the anvil holder in place..


DISASSEMBLY:

Reverse assembly instructions.

WARNING:

EXPOSED MOVING PARTS. KEEP HANDS OFF DURING OPERATION TO PREVENT PERSONAL INJURY.

1. APPLY LOCTITE® C5-A® ANTI-SIEZE LUBRICANT (408183) OR EQUIVALENT TO OUTSIDE OF PULLER AND INSIDE DIAMETER OF ANVIL.



11/23 REV 2/26



GAGE BILT
 MADE in USA

44766 Centre Court, Clinton Twp., MI. 48038 USA
 Ph: +1 (586) 226-1500 Fax: +1 (586) 226-1505
 solutions1@gagebilt.com / www.gagebilt.com

Type:		Fasteners:		Recommended Tool: GB20SF
Self-Releasing 12mmØ		NeoBolt® Lockbolt		
Ref. No.	Qty.	Description		NB12MM- 20SF-41
1	1	Anvil Assembly		112-0001
2	1	Anvil Holder		11272
3	1	Puller		31249
4	1	Nut		72007
5	1	Extension-Puller		71251

NEOBOLT® IS A REGISTERED TRADEMARK OF AVDEL UK LIMITED. LOCTITE® AND C5-A® ARE REGISTERED TRADEMARKS OF HENKEL CORPORATION U.S.A.