



NOSE ASSEMBLY DATA SHEET



Slots on retaining nut stop, supplied with tool, fit over ears on anvil assembly



11/15 Rev. 3/25

ASSEMBLY:

Notes:

- Apply Vibra-tite® p/n/ 405125 to all threads and allow it to set 20 minutes prior to assembly.
- Tighten collet (2) and extension-collet (4) to 80 - 100 IN-LBS. (.36 - .44 Kn) torque.
- If nose assy is assembled as it is when purchased new, follow steps 3 - 5 to attach to tool.
 - Insert super grip jaw assy (3) into rear of collet (4). (Note direction in exploded view).
 - Thread collet (2) to extension-collet (4) using flats provided.
 - Thread assembled collet (2) and extension-collet (4) onto piston of tool using flats provided and hex in rear of piston.
 - Slide anvil (1) over collet (2).
 - Slide retaining nut stop and retaining nut over ears on anvil (see exploded view) and tighten to tool.

DISASSEMBLY:

Reverse assembly instructions.

*Anvil Assembly includes 35308 retainer.

**Yellow band designates nose assemblies for lightweight GP® fasteners

GAGE BILT
MADE in USA

44766 Centre Court Clinton Twp. MI 48038 USA
Ph: +1 (586) 226-1500 Fax: +1 (586) 226-1505
solutions1@gagebilt.com / www.gagebilt.com

Type:		Fasteners:		Recommended Tool: GB745	
Non Self-Releasing 3/16" Ø		LGP® lockbolts ASNA2391-3 ASNA2392-3		Alternate Tools: GB756 & GB2581(A)	
Ref. No.	Qty.	Description		LGP06-2581-23	
1	1	Anvil		16612	
2	1	Collet		20655	
3	1	Super-Grip Jaw Assy		30651-S	
4	1	Extension-Collet		70635	

GP® AND LGP® ARE REGISTERED TRADEMARKS OF HOWMET AEROSPACE. VIBRA-TITE® IS A REGISTERED TRADEMARK OF OAKLAND CORPORATION.