



NOSE ASSEMBLY DATA SHEET



Slots on retaining nut stop, supplied with tool, fit over ears on anvil assembly



ASSEMBLY:

Notes:

- Apply Vibra-tite® p/n/ 405125 to all threads and allow it to set 20 minutes prior to assembly.
 - Tighten collet (2) and extension-collet (4) to 80-100 IN-LBS. (.36 - .44 Kn) torque.
 - If nose assembly is assembled as it is when purchased new, follow steps 3-5 to attach to tool.
- Insert super grip jaw assembly (3) into rear of collet (2). (Note direction in exploded view).
 - Thread collet (2) to extension-collet (4) using hex key in front of collet-extension (4) and flats provided on collet (2).
 - Thread assembled collet (2) and extension-collet (4) onto piston of tool using flats provided and hex in rear of piston.
 - Slide anvil assembly (1) over collet (2).
 - Slide retaining nut stop and retaining nut over ears on anvil (see exploded view) and tighten to tool.

DISASSEMBLY:

Reverse assembly instructions.



12/24

GAGE BILT
MADE in USA

44766 Centre Court Clinton Twp. MI 48038 USA
Ph: +1 (586) 226-1500 Fax: +1 (586) 226-1505
solutions1@gagebilt.com / www.gagebilt.com

Type:		Fastener:	Recommended Tool:
Non Self-Releasing 5/32" Ø		NAS Tension Pull Type Lockbolts, C6L® & GP® Lockbolts	GB731
Ref. No.	Qty.	Description	NAST05-2480-45CN
1	1	Anvil Assembly	10575
2	1	Collet	20414
3	1	Super-Grip Jaw Assembly	30542-S
4	1	Extension-Collet	70551