






NOSE ASSEMBLY DATA SHEET



1 APPLY LOCTITE® C5-A® ANTI-SEIZE LUBRICANT (408183) OR EQUIVALENT TO OUTSIDE OF PULLER AND INSIDE DIAMETER OF ANVIL.



ASSEMBLY:

Notes:

1. Thread nut (3) onto puller (2) as shown in dimensional view..
2. Thread assembled puller (2) in tool's end cap.
3. Collapse puller and tighten nut (3) using wrench part # 200160.
4. Install anvil assy. (1) over puller (2) and thread into tool's piston.
5. Tighten anvil assy. using a spanner wrench.

DISASSEMBLY:

Reverse assembly instructions.

9/23 REV 10/24



GAGE BILT
MADE in USA

44766 Centre Court Clinton Twp. MI 48038 USA
Ph: +1 (586) 226-1500 Fax: +1 (586) 226-1505
solutions1@gagebilt.com / www.gagebilt.com

Type:		Fasteners:		Recommended Tool: GB20SF
Self-Releasing		Meishan Bolt 1/2" & 12mm Diameter		
Ref. No.	Qty.	Description		MSB12MM-20SF-10
1	1	Anvil Assembly		11277
2	1	Puller		31248
3	1	Nut		72007