


NOSE ASSEMBLY DATA SHEET




CAUTION:

Do not operate if pintail deflector is removed. Pintail may eject forcibly. SEVERE PERSONAL INJURY MAY RESULT.

Attachment

Screw nose assembly onto tool until it stops then back off until nose is in desired position. (Warning: do not back off nose assembly more than one complete turn). Lock jam nut (70336) against adapter (70332)

WARNING:
KEEP FINGERS AND HANDS AWAY
FROM NOSE ASSEMBLY DURING
OPERATION TO PREVENT SEVERE
PERSONAL INJURY.



Cap (5) is used for closed access applications only or when clearance is an issue.

9/06 Rev. 12/15



**USE ADAPTER 745751 & DO NOT USE # (7) JAM NUT 70336.

GAGE BILT
MADE IN U.S.A.

GAGE BILT Inc.

44766 Centre Court (586) 226-1500
Clinton Twp. MI 48038 (586) 226-1505 Fax
e-mail:solutions@gagebilt.com / www.gagebilt.com

Type:		Fasteners:		Recommended Tool:	
Non Self-Releasing *1/8" Ø		NAS1398A/1399A RV 1000/1100 & 1200 *5/32 Ø AF5075 / AF5076 / S149A020		GB751	
				Alternate Tools: GB722 & **GB745	
Ref. No.	Qty.	Description		4A-752A-43OS	
1	1	Anvil Insert		10488	
2	1	Anvil & Holder Assy (Inc. #1)		12217	
3	1	Collet		20911	
4	1	Super-Grip Jaw Assy		30425-S2	
5	1	Cap		60428	
6	1	Anvil Adapter		70331	
7	1	Jam Nut		70336	
8	1	Pin		70468	
9	1	Collet Adapter		70332	
10	1	Barbed Retainer		60440	
11	1	Deflector		61107	