


NOSE ASSEMBLY DATA SHEET




ASSEMBLY:

Notes:

- Apply Vibra-tite® p/n/ 405125 to all threads and allow it to set 20 minutes prior to assembly.
- Tighten collet (3) and extension-collet (5) to 80-100 IN-LBS. (.36 - .44 Kn) torque.
- If nose assy is assembled as it is when purchased new, follow steps 3-5 to attach to tool.
 - Insert super grip jaw assy (4) into rear of collet (3).
 - Thread collet (3) to extension-collet (5) using flats provided.
 - Thread assembled collet (3) and extension-collet (5) onto piston of tool using flats provided and hex in rear of piston.
 - Slide anvil & holder assembly (2) over collet (3).
 - Slide retaining nut stop and retaining nut over ears on anvil (see exploded view) and tighten to tool.

DISASSEMBLY:

Reverse assembly instructions.



1/02 Rev. 6/25

*Anvil & Holder Assembly consists of #1 and 35208 retainer

GAGE BILT
MADE in USA

44766 Centre Court Clinton Twp. MI 48038 USA
Ph: +1 (586) 226-1500 Fax: +1 (586) 226-1505
solutions1@gagebilt.com / www.gagebilt.com

Type:		Fastener:	Recommended Tool:
Non Self-Releasing 1/4" Ø		NAS9301-NAS9312 M7885 BACR15FP/FR BACR15GF/GK	GB722
			Alternate Tools: GB752 & GB2480(A)
Ref. No.	Qty.	Description	08MAX-752B-20
1	1	Anvil-Driving	18009
2	1	*Anvil & Holder Assembly (Inc. #1)	17767
3	1	Collet	20717
4	1	Super-Grip Jaw Assembly	30864-S
5	1	Extension-Collet	70550