


NOSE ASSEMBLY DATA SHEET




CAUTION:

Do not operate if pintail deflector is removed. Pintail may eject forcibly. SEVERE PERSONAL INJURY MAY RESULT.

Attachment

Screw nose assembly onto tool until it stops then back off until nose is in desired position. (Warning: do not back off nose assembly more than one complete turn). Lock jam nut (70411) against adapter (70341)

WARNING:
KEEP FINGERS AND HANDS AWAY FROM NOSE ASSEMBLY DURING OPERATION TO PREVENT SEVERE PERSONAL INJURY.



Cap (5) is used for closed access applications only or when clearance is an issue.



9/06 Rev. 4/15

GAGE BILT
MADE IN U.S.A.

GAGE BILT Inc.

44766 Centre Court (586) 226-1500
Clinton Twp. MI 48038 (586) 226-1505 Fax
e-mail:solutions@gagebilt.com / www.gagebilt.com

Type:		Fasteners:	Recommended Tool: GB715
Non Self-Releasing 10-32 Ø		Grounding Stud	Alternate Tools: GB51
Ref. No.	Qty.	Description	GS10-715A-400S
1	1	Anvil-Driving	10268
2	1	Anvil Holder	13368
3	1	Collet	20911
4	1	Super-Grip Jaw Assy	30656-S3
5	1	Cap	60428
6	1	Pin	70468
7	1	Anvil Adapter	70341
8	1	Jam Nut	70411
9	1	Collet Adapter	70340
10	1	Barbed Retainer	60440
11	1	Deflector	61107