



NOSE ASSEMBLY DATA SHEET



ASSEMBLY:

Note:

- Apply Vibra-tite® p/n 405125 to all threads and allow it to set 20 minutes prior to assembly.
- Tighten extension-collet (6) to piston on tool 80-100 IN-LB torque.
- If nose assy is assembled as it is when purchased new, follow steps 3-5 to attach to tool.
 - Insert super grip jaw assembly (5) into collet (4).
 - Tighten extension-collet (6) and collet (4) together using flats provided.
 - Thread assembled collet (4) and extension -collet (6) to piston on tool. Tighten assembled parts using 9/16" wrench on extension-collet (6) and hex key in rear of piston on tool.
- Slide anvil & holder assembly (1) over assembled collet (4) and extension-collet (6).
- Slide Retaining nut on anvil & holder assembly (1) and tighten. (Note: Retaining nut stop not used in this nose assembly).

DISASSEMBLY:

Reverse assembly instructions.

10/19 REV 9/25



GAGE BILT
MADE in USA

44766 Centre Court Clinton Twp. MI 48038 USA
Ph: +1 (586) 226-1500 Fax: +1 (586) 226-1505
solutions1@gagebilt.com / www.gagebilt.com

Type:		Fasteners:	Recommended Tool: GB745
Non Self-Releasing 3/16" Ø		MAGNA-GRIP®, MULTI-GRIP, MAXLOK® LOCKBOLTS	Alternate Tools: GB756 & GB2581(A)
Ref. No.	Qty.	Description	MG06-745-24
1	1	Anvil & Holder Assembly (Incl. #2 & #3)	16038
2	1	Anvil-Insert	16634
3	1	Anvil Holder	12387-1
4	1	Collet	20636
5	1	Super-Grip Jaw Assembly	30652-S
6	1	Extension-Collet	70832

MAGNA-GRIP® IS A REGISTERED TRADEMARK OF HOWMET AEROSPACE. MAXLOK® IS A REGISTERED TRADEMARK OF AVDEL UK LIMITED. VIBRA-TITE® IS A REGISTERED TRADEMARK OF OAKLAND CORPORATION.