



NOSE ASSEMBLY DATA SHEET



NOTE!

Use with driver: ASP-05

SLOTS ON RETAINING
NUT STOP, SUPPLIED
WITH TOOL, FIT OVER



ASSEMBLE
DRIVING ANVIL
WITH C'BORE
FACING OUT



ASSEMBLY:

Notes:

- Apply Vibra-tite® p/n/ 405125 to all threads and allow it to set 20 minutes prior to assembly.
 - Tighten collet (3) and extension-collet (6) to 80 - 100 IN-LBS. (.36 - .44 Kn) torque.
 - If nose assy is assembled as it is when purchased new, follow steps 3 - 5 to attach to tool.
- Insert super grip jaw assy (4) into rear of collet (3). Place spacer (5) on rear of super grip jaw assy (4)
 - Thread collet (3) to extension-collet (6) using flats provided.
 - Thread assembled collet (3) and extension-collet (6) onto piston of tool using flats provided and hex in rear of piston.
 - Slide anvil & holder assembly (2) over collet (3).
 - Slide retaining nut stop and retaining nut over ears on anvil (see exploded view) and tighten to tool.

DISASSEMBLY:

Reverse assembly instructions.

1/12 REV 10/25

GAGE BILT
MADE in USA

44766 Centre Court Clinton Twp. MI 48038 USA
Ph: +1 (586) 226-1500 Fax: +1 (586) 226-1505
solutions1@gagebilt.com / www.gagebilt.com

Type:		Fastener:	Recommended Tool:
Non Self-Releasing 11/64"		ASP® ASP 2, ASP PF, ASP 2 F, ASP 2 LC, ASP 4 FF, ASP FF, ASP F, ASP-LC and MAF	GB751
			Alternate Tools: GB713,GB722, GB752 & GB2480(A)
Ref. No.	Qty.	Description	ASP05-752C-45
1	1	Driving Anvil	15581
2	1	Anvil & Holder Assembly	13417
3	1	Collet	20727
4	1	Super-Grip Jaw Assembly	30425-S
5	1	Spacer	40465
6	1	Extension-Collet	70551

ASP® IS A REGISTERED TRADEMARK OF HOWMET AEROSPACE. VIBRA-TITE® IS A REGISTERED TRADEMARK OF OAKLAND CORPORATION.