


NOSE ASSEMBLY DATA SHEET




ASSEMBLY:

Notes:

- A. Apply Vibra-tite® p/n/ 405125 to all threads and allow it to set 20 minutes prior to assembly.
- B. If nose assy is assembled as it is when purchased new, follow steps 3-5 to attach to tool.
1. Insert super grip jaw assy (5) into rear of collet (4). (Note direction in exploded view).
2. Thread collet (4) to piston on tool using flats provided.
3. Slide anvil & holder assy (1) over collet (4).
4. Slide retaining nut over ears on anvil and tighten to tool. (Note: retaining nut stop not used with this nose assembly).

DISASSEMBLY:

Reverse assembly instructions.



10/22

GAGE BILT
MADE in USA

44766 Centre Court Clinton Twp. MI 48038 USA
Ph: +1 (586) 226-1500 Fax: +1 (586) 226-1505
solutions1@gagebilt.com / www.gagebilt.com

Type:		Fasteners:		Recommended Tool: GB2480L
Non Self-Releasing 3/16" Ø		Commercial Lockbolt C6L®, Avdelok®		
Ref. No.	Qty.	Description		LB06-722-20L
1	1	Anvil & Holder Assy		16002
2	1	Anvil		16003
3	1	Holder		12242-3
4	1	Collet		20636
5	1	Super-Grip Jaw Assy		30653-CS

C6L® IS A REGISTERED TRADEMARK OF HOWMET AEROSPACE. AVDELOK® IS A REGISTERED TRADEMARK OF AVDEL UK LIMITED. VIBRA-TITE® IS A REGISTERED TRADEMARK OF OAKLAND CORPORATION.