




# NOSE ASSEMBLY DATA SHEET



**CAUTION:**  
Pintail may eject forcibly. USE DEFLECTOR TO PREVENT SEVERE PERSONAL INJURY.



**WARNING:**  
DO NOT REMOVE - PINCH POINT

## NOTES:

1. In wet applications where sealant is used: 30543 jaw assy, 40688 follower, 405717 spring & 60628 locator may be ordered for easier cleaning of sealant from jaws.
2. Nose assembly shipped with 60447 stop.
3. Yellow designates nose assemblies for lightweight GP® fasteners.

## ATTACHING NOSE ASSEMBLY TO TOOL:

1. Cycle tool to ensure piston is full forward.
2. Disconnect tool from power source.
3. Remove screw and stop from tool.
4. Apply Vibra-TITE® part no. 405124 to threads on drawbar.
5. With nose assembly completely assembled, hold collet full forward in anvil and thread drawbar into piston.
6. In approximately 2-3 turns, the anvil assy threads will also engage onto tool, continue to thread drawbar and anvil completely on tool.
7. Back-off assy, no more than 1/2 turn, to position notch on anvil allowing screw and stop to be reassembled onto tool.



\*Use Adapter No. 751206-1 & 731158 stroke limiter.  
Optional use 731206 (No stroke limiter needed).

\*\*Use Adapter No. 353206-1 & 745160 stroke limiter.

7/23

**GAGE BILT**  
MADE in USA

44766 Centre Court Clinton Twp. MI 48038 USA  
Ph: +1 (586) 226-1500 Fax: +1 (586) 226-1505  
solutions1@gagebilt.com / www.gagebilt.com

| Type:                         |      | Fasteners:                                | Recommended Tool:                                              |
|-------------------------------|------|-------------------------------------------|----------------------------------------------------------------|
| Non Self-Releasing<br>5/32" Ø |      | LGP® Lockbolt<br>ASNA2391-2<br>ASNA2392-2 | GB206-500(A)                                                   |
|                               |      |                                           | Alternate Tools:<br>*GB731, GB731OS/206,<br>**GB745 & GB110AOS |
| Ref. No.                      | Qty. | Description                               | LGP05-34OSSG                                                   |
| 1                             | 1    | Anvil                                     | 15013                                                          |
| 2                             | 1    | Collet Cartridge                          | 20599                                                          |
| 3                             | 1    | Guard                                     | 60443                                                          |
| 4                             | 1    | Super Grip Jaw Assembly                   | 30543-S9                                                       |
| 5                             | 1    | Collet Housing                            | 20743                                                          |
| 6                             | 1    | Barbed Retainer                           | 70580                                                          |
| 7                             | 1    | Deflector                                 | 61107                                                          |
| 8                             | 1    | Backguard                                 | 60444                                                          |
| 9                             | 1    | Drawbar                                   | 71153                                                          |
| 10                            | 2    | Button Head Cap Screw                     | 408511                                                         |