



NOSE ASSEMBLY DATA SHEET



Slots on retaining nut stop, supplied with tool, fit over ears on anvil assembly



ASSEMBLY:

Notes:

- Apply Vibra-tite® p/n/ 405125 to all threads and allow it to set 20 minutes prior to assembly.
 - Tighten collet (2) and extension-collet (7) to 80-100 IN-LB torque.
 - If nose assy is assembled as it is when purchased new, follow steps 4-5 to attach to tool.
- Insert super grip jaw assy (3) onto barbed guide (4). Insert spring (6) into rear of barbed guide (4). Place into rear of collet (2).
 - Align hole in barbed guide (4) with slot in collet (2). Insert cross pin (5) thru slot of collet (2) and into barbed guide (4).
 - Thread collet (2) to extension-collet (7) using hex key in front of collet-extension (7) and flats provided on collet (2).
 - Thread assembled collet (2) and extension-collet (7) to piston on tool using hex in rear of piston and flats provided on collet (2).
 - Slide anvil assy (1) over assembled collet (2) then slide retaining nut stop and retaining nut over ears on anvil and tighten to tool.

DISASSEMBLY:

Reverse assembly instructions.

*Pull-in applications require the installation tool to be operated at a lower psi air pressure so the pintail doesn't break off. Air pressure recommendations below are for titanium fasteners only. Refer to fastener manufacturer for formula to figure air pressure required for all other materials. Pre-set regulators are available please contact Gage Bilt. When using hydraulic tool contact Gage Bilt for powerunit settings.



11/14 REV 8/24

**Anvil Assembly includes 35208 retainer.

***White band designates nose assemblies for pull-in fasteners.

GAGE BILT
MADE in USA

44766 Centre Court Clinton Twp. MI 48038 USA
Ph: +1 (586) 226-1500 Fax: +1 (586) 226-1505
solutions1@gagebilt.com / www.gagebilt.com

Type:		Fasteners:	Recommended Tool:
Self-Releasing 1/4" Ø		LGP® Lockbolts ASNA2391-4 ASNA2392-4	*GB745 (41 psi)
			Alternate Tools: *GB756 (26 psi)
Ref. No.	Qty.	Description	LGP08-745-24PI
1	1	Anvil Assy	18001
2	1	Collet	28839
3	1	Super-Grip Jaw Assy	30877-CS
4	1	Barbed Guide	48815
5	1	Cross Pin	70890
6	1	Spring	406031
7	1	Extension-Collet	70891