



NOSE ASSEMBLY DATA SHEET



CAUTION:
Pintail may eject forcibly. USE DEFLECTOR TO PREVENT SEVERE PERSONAL INJURY. Cap (8) use for closed access applications only or when clearance is an issue!

Nose Assy.	A	B	C
LGP05-	3.29 (83.5mm)	2.22 (56.3mm)	.92 (23.3)
LGP06-	3.31 (84mm)	2.24 (57mm)	.94 (24mm)
LGP07-	3.35 (85.1mm)	2.28 (57.9mm)	.98 (24.8mm)
LGP08-	3.35 (85.1mm)	2.28 (57.9mm)	.98 (24.8mm)



WARNING:
DO NOT REMOVE - PINCH POINT

ATTACHING NOSE ASSEMBLY TO TOOL:

1. Cycle tool to ensure piston is full forward.
2. Disconnect tool from power source.
3. Remove screw and stop from tool.
4. Apply Vibra-TITE® part no. 405124 to threads on drawbar.
5. With nose assembly complete assembled, hold collet full forward in anvil and thread drawbar into piston.
6. In approximately 2-3 turns, the anvil assy threads will also engage onto tool, continue to thread drawbar and anvil completely on tool.
7. Back-off assy, no more than 1/2 turn, to position notch on anvil allowing screw and stop to be reassembled onto tool.

NOTE:

Yellow logo designates nose assy's for lightweight GP® fasteners.

Rev. 2/23



*Use Adapter No. 751206.

**Use Adapter No. 353206.

GAGE BILT
MADE in USA

44766 Centre Court Clinton Twp. MI 48038 USA
Ph: +1 (586) 226-1500 Fax: +1 (586) 226-1505
solutions1@gagebilt.com / www.gagebilt.com

Type:		Fasteners:		Recommended Tool: GB206-500(A)		
Non Self-Releasing 5/32", 3/16", 7/32" & 1/4" Ø		LGP® Lockbolt		Alternate Tools: *GB731 & **GB745		
Ref. No.	Qty.	Description	LGP05-206G-34OS	LGP06-206G-34OS	LGP07-206G-34OS	LGP08-206G-34OS
1	1	Anvil Assy	15543	16639	17003	18832
2	1	Guard	60426	60426	60426	60426
3	1	Collet	20554	20673	20732	20890
4	1	Super-Grip Jaw Assy	30543-S9	30654-S9	30702-S1	30862-S5
5	1	Barbed Retainer	70569	70569	70569	70569
6	1	Deflector	61107	61107	61107	61107
7	1	Drawbar	71142	71142	71142	71142
8	1	Cap	70571	70571	70571	70571